

323754 Product Details



323754

TE Internal Number: 323754

 [Active](#)

 [View 3D PDF](#)

Splices - Closed Barrel

 [Always EU RoHS/ELV Compliant](#)
([Statement of Compliance](#))

Product Highlights:

- Splice
- Not Sealed
- Splice Type = Parallel
- Body Style = SOLISTRAND, STRATO-THERM
- Uninsulated

[View all Features](#)

Documentation & Additional Information

Product Drawings:

- [SPLICE, PARALLEL, HEAT RESISTANT, STRATO-THERM@PZTM](#) (PDF, English)

Catalog Pages/Data Sheets:

- [AEROSPACE & DEFENSE](#) (PDF, English)
- [STRATO-THERM TERMINALS& SPLICES FOR HIGH TEMP APPL](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version C)
- [3D Model](#) (IGES, Version C)
- [3D Model](#) (STEP, Version C)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Splice
- [Sealed](#) = No
- [Splice Type](#) = Parallel
- [Body Style](#) = SOLISTRAND, STRATO-THERM
- [Insulation](#) = No
- [Insulation Support](#) = Non-Insulation Support
- [Material](#) = Copper
- [Finish](#) = Nickel
- Color = None
- Tongue Material Thickness (mm [in]) = 1.07 [0.042]

Mechanical Attachment:

- Inside Diameter (mm [in]) = 3.28 [0.129]

Industry Standards:

- Government/Industry Qualification = No
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- High Temperature Rating (°C [°F]) = 343 [650]

Packaging Related Features:

- [Packaging Method](#) = Loose Piece

Other:

- Brand = AMP

Body Related Features:

- [Wire Range \(mm \[AWG\]\)](#) = 3.00-6.00² [12-10]
- [Wire Range \(CMA\)](#) = 5,180 – 13,100
- Outside Diameter (mm [in]) = 5.74 [0.226]