


353908-2 Product Details

Have a Question?

Chat with a Product Information Specialist



353908-2

TE Internal Number: 353908-2

 [Active](#)

 [View 3D PDF](#)

1.5mm AMP Mini CT Connectors

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Connector
- Wire-to-Board, Wire-to-Board/Wire-to-Wire/Wire-to-Panel, Wire-to-Panel, Wire-to-Wire
- Applies To Wire
- 1.50 mm Centerline
- Housing

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [View Mating Products \(5\)](#)
- ▶ [View Contacts \(2\)](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

 [Add to My Part List](#) |
  [Request Sample](#) |
  [Find Similar Products](#) |
  [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [AMP MINI COMMON TERMINATED \(CT\) CONNECTOR 1.5mm PIT...](#) (PDF, English)

Catalog Pages/Data Sheets:

- [REPRESENTATIVE TERMINALS AND CONNECTORS](#) (PDF, English)
- [PERSONAL SYSTEMS PRODUCTS](#) (PDF, English)

Product Specifications:

- [AMP Mini Common Termination \(CT\) Connector 1.5mm Pit...](#) (PDF, English)
- [AMP Mini CT Connector 1.5mm Pitch \(Crimp Type\), Lead...](#) (PDF, Japanese)

Application Specifications:

- [AMP MINI COMMON TERMINATION \(CT\) CONNECTOR, 1.5MM PI...](#) (PDF, English)

Instruction Sheets:

- [1.5mm Pitch Mini CT DC Drawer Connector SF Type](#) (PDF, Japanese)
- [1.5mm Pitch Mini CT Hybrid Drawer Connector SF Type](#) (PDF, Japanese)
- [1.5mm Pitch Mini CT Hybrid Drawer Connector Slim Type](#) (PDF, Japanese)

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version B)
- [3D Model](#) (IGES, Version B)
- [3D Model](#) (STEP, Version B)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)
- [Mating Products \(5\)](#)
- [Contacts \(2\)](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Connector Type = Housing
- Termination Method to Wire/Cable = Crimp
- CSA File Number = LR 7189-133

Electrical Characteristics:

- Contact Current Rating (A) = 2
- Operating Voltage Reference = AC/DC
- Operating Voltage (V) = 50

Body Related Features:

- Centerline (mm [in]) = 1.50 [0.059]
- [Number of Positions](#) = 2
- [Number of Rows](#) = 1
- Length (X-Axis) (mm [in]) = 4.50 [0.1772]
- Width (Z-Axis) (mm [in]) = 3.60 [0.141]
- Profile Height (Y-Axis) (mm [in]) = 6.00 [0.236]

Contact Related Features:

- Contact Type = Socket

Housing Related Features:

- Housing Color = Natural
- UL Flammability Rating = UL 94V-0

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- UL Rating = E28476

Conditions for Usage:

- Applies To = Wire
- Operating Temperature (°C [°F]) = -30 - +105 [-22 - +221]
- Accepts Wire Insulation Diameter, Range (mm [in]) = 0.85 - 1.05 [0.0334 - 0.041]

Operation/Application:

- Application Use = Wire-to-Board, Wire-to-Board/Wire-to-Wire/Wire-to-Panel, Wire-to-Panel, Wire-to-Wire
- Pick and Place Cover = Without

Packaging Related Features:

- Packaging Method = Box

Other:

- Brand = AMP

 [BOOKMARK](#)   

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat with Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage Your Account](#)

Sign up for our eNewsletter

Enter your email address 

Follow Us On:



Visit Us On:

