




BNC Connectors, 50 Ohm (Continued)

Plugs, Solder/Clamp



H = 12.7 [0.500] Max. across flats.
14.74 [0.580] Max. across points.



Maximum PC Board Thickness 2.11 [0.083]
Recommended Panel Cutout for Push-On Style


RG/U Cable	Center Contact Plating	Body Plating	Dielectric	Style	M/A-COM Model No.	Dim. L	Part No.
RG174A/U, RG188A/U, RG316/U, URM95	Gold	Silver	TEFLON	Mil Type	B35A70E022X	28.5 1.122	1310700-1
	Gold	Nickel	TEFLON	Mil Type	B35A70J022X	28.5 1.122	1310705-1
RG179B/U, RG187A/U, URM111	Gold	Silver	TEFLON	Mil Type	B37A70F022X	28.5 1.122	1311685-1
RG58C/U, RG141A/U, URM43, URM76	Gold	Silver	TEFLON	Mil Type	B35A70E010X	28.5 1.122	1310697-1
	Gold	Nickel	TEFLON	Mil Type	B35A70J010X	28.5 1.122	1310702-1
58, 58A, 58B, 58C	Gold	Nickel	TEFLON	Push-On	—	26.04 1.025	222728-1
RG55B/U, RG142B/U, RG223/U, RG400/U, URM301	Gold	Silver	TEFLON	Mil Type	B35A70E060X	28.5 1.122	1312559-1
	Gold	Nickel	TEFLON	Mil Type	B35A70J060X	28.5 1.122	1311674-1
RG59B/U, RG62A/U, RG140/U, TM3304	Gold	Silver	TEFLON	Mil Type	B37A70E025X	28.5 1.122	1310776-1
	Gold	Nickel	TEFLON	Mil Type	B37A70J025X	28.5 1.122	1310777-1
PSF1/4(BBC), RG8A/U, RG213A/U, URM67	Gold	Silver	TEFLON	Mil Type	B35A03E001X	38.1 1.500	1314882-1
	Gold	Nickel	TEFLON	Mil Type	B35A03J001X	38.1 1.500	1310690-1
URM70	Gold	Silver	TEFLON	Mil Type	B37A70E012X	28.5 1.122	1310775-1
BT2003, BT2003A	Gold	Silver	TEFLON	Mil Type	B37A70E062X	28.5 1.122	1314874-1
BT2002	Gold	Silver	TEFLON	Mil Type	B37A70E117X	28.5 1.122	1314875-1

Plugs, Twist-On

Related Product Data

Twist-On plugs must be used with cable that has a solid conductor. These plugs are not recommended for applications where the cable frequently moves or flexes.

Mating Twist-On Jack — Page 51



RG/U Cable	Contact Plating	Body Plating	Dielectric	Style	Part No.
58, 58B	Gold	Nickel	Polymethyl-pentene	Commercial	414265-7
59, 59A, 59B	Gold	Nickel	Polymethyl-pentene	Commercial	414265-3
Beiden 8281, 9141, 9231, Western Electric 724, 723, 3049	Gold	Nickel	Polymethyl-pentene	Commercial	414265-5