

What can we help you find?

	••	E My Ac		Innovation	
207719-3 Product Deta			Share	🗎 Print	ጆ Email
S207719-3 TE Internal Number: 5207719-3 Active	 Hardware (AMPLIMITE) Always EU RoHS/ELV Co (Statement of Compliance) Product Highlights: Accessory Type = Female Assembly Kit Clear Chromate Body Fini Thread Size = 4-40 Thread Length = 14.22 m Screw Length = 18.99 mr View all Features 	Screwlock sh m	 Search Produce 	inks 9 & Availability n for Tooling ct Feature Sele ct Us About Th	ector
	Add to My Part List Buy Product	<u>Request Sa</u>	<u>mple Fin</u>	<u>d Similar Produ</u>	<u>ucts</u>
Oocumentation & Additional Inf	ormation				
Product Drawings: SCREWLOCK FEMALE ASSEMBLY, AMPLIMITE (PDF, English)			Additional Information: • Product Line Information		ion
Catalog Pages/Data Sheets: AMPLIMITE Subminiature D (English) Product Specifications: None Available Application Specifications: None Available Enstruction Sheets: Female Screwlock Kits and M CAD Files: (CAD Format & Compre 2D Drawing (DXF, Version O) 3D Model (IGES, Version O) 3D Model (STEP, Version O)	lale Screw Retainer Kits (PDF, E ssion Information)	(PDF,	Related Prod • Tooling		
	List all [Documents			
 Product Features (Please use the Product Type Features: Accessory Type = Female Sc Thread Size = 4-40 Dimensions: Screw Length (mm [in]) = 18 Body Features: Body Finish = Clear Chromate 	rewlock Assembly Kit 8.99 [0.748] e 14.22 [0.560] Conc	stry Standa Governmen RoHS/ELV C compliant Lead Free S free process RoHS/ELV C compliant litions for Us For Use Wit	rds: t/Industry Qua compliance = F older Processe compliance His sage:	alification = No RoHS complian es = Not releva story = Always Connectors wit	t, ELV ant for lead was RoHS

Have a Question? Chat with a Product Information Specialist

 Brand 	= AMP
---------------------------	-------

 Comment = Short female screwlocks cannot be used with HDF connectors.; Female screwlocks mate with male screw retainers.; Female screwlocks with 2-56 thread size are to be used with cable clamps with mounting flanges. Female screwlocks with 4-40 and M3 (Metric) thread sizes can be used with all other cable clamps.; Each female screwlock kit is comprised of two assemblies.; All parts are packaged unassembled.; One or two flat washers may be required for panel thicknesses less than 1.52 [.060]. Female screwlocks are not recommended for panel thicknesses greater than 1.52 [.060].

Corporate Information About TE Investors News Room Supplier Portal Careers Terms & Conditions Privacy Policy

Quick Links


Distributor Inventory Product Cross Reference Documents & Drawings Product Compliance Support Center Site Map **Customer Support** Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

Keep Me Informed



© 2013 Tyco Electronics Corporation, a TE Connectivity Ltd. company. All Rights Reserve

Provide Website Feedback



REVISIONS					
DESCRIPTION		DATE	DWN	APVD	
0-11-004835		11MAR11	RK	HMR	
					C
\bigwedge		5207	710		В
$\frac{2}{2}$					
4		5207			
<u>/</u> <u>}</u>		5207			
/4	/1\	5207	/19	_	
		PA	RT		
KAGING	FINISH	NUM	BER		
ST	E TE Conr	nectivity			
		,			
SC	REWLOCK FEM	ALE			
	SEMBLY, AMPLII				A
	_				/ \
AGE CODE DRAWING			RESTRIC	TED TO	
0779 C- 5				-	
	SCALE 4:1 St	HEET 1 OF 1	REV	Ρ	
	I				