



Electronics

a vital part of your world

Find Answers:

Friday, 18 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

.100 & .200 Centerline DIN 41612 Connectors (Eurocard)

↳ Eurocard Type C and Enhanced Type C Connectors .100 Centerline - 3 Row

AMP 535089-5 Active

Directive 2000/53/EC Compliant

ELV Compliant

(Corporate P/N: 535089-5)

Search for Compliant (RoHS/ELV) Alternates
CAD Geometry | Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> General Info Sales Info Assembly Subcontractors 	<ul style="list-style-type: none"> Pricing & Availability 	<ul style="list-style-type: none"> Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	ELV compliant
Lead Free Solder Processes:	Wave solder capable to 240°C
Product Type:	Type C Connectors
Gender:	Receptacle
Number of Positions:	96
Rows Loaded:	A, B, C
Terminate To:	Printed Circuit Board
Special PCB Retention:	No
PCB Mount Angle:	Vertical
Post Type:	Solder Post

Other Properties:

RoHS/ELV Compliance History:	Always was ELV compliant
Toolless (Flat Rock):	No
Contact Material:	Phosphor Bronze
Housing Material:	Polyester
Color:	Gray
Housing Flammability Rating:	UL 94V-0

<u>Termination Post Length (mm [in]):</u>	2.49 [0.098]
<u>Size:</u>	Standard
<u>Contact Cross Section (mm [in]):</u>	0.30 x 0.61 [.012 x .024]
<u>Make First / Break Last:</u>	No
<u>Bus Type:</u>	FUTUREBUS, MULTIBUS (II), NUBUS, VMEbus, VXIBus
<u>DIN Level:</u>	II
<u>Mounting Ears:</u>	With
<u>High Temperature Housing:</u>	No
<u>Flux-Tight Coating:</u>	Without

[Copyright and Privacy Statement](#)
Visit Tyco International Ltd.

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]