



RIBBON CABLE CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

A/L UNIV HDR 34P RA LG LAT

AMP-LATCH | Universal Headers

5499141-8

TE Internal Number: 5499141-8

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

PCB Mount Retention **Without**

PCB Mounting Orientation **Right Angle**

Termination Method to PC Board **Through Hole**

Shrouded **Yes**

Product Drawings

[HEADER ASSY, UNIVERSAL, AMP-LATCH](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[Ribbon Cable Interconnect Solutions](#)

PDF
English

Product Specifications

Product Specification

[AMP-LATCH And IDC Header Connectors, .100 X .100 Inch Grid](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_5499141-8_0318201592_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Right Angle
	Shrouded	Yes
	Row-to-Row Spacing	2.54 mm [.1 in]
	Connector Style	Plug
	Profile	Standard
	Product Type	Connector
	Board Standoff	Without
	Connector System	Wire-to-Board
	Ejection Latches	With
	Applies To	Printed Circuit Board
	Connector Type	Header
Latch Type	Long	

Configuration Features	Number of Positions	34
	Number of Rows	2

Electrical Characteristics	Operating Voltage (VAC)	250
	Insulation Resistance (MΩ)	5000

Body Features	Post Size	.64 mm [.025 in]
	Header Type	Universal Ejection Pin Headers

Contact Features	Contact Design	Square Post
	Contact Transmits (Typical)	Signal (Data)
	Contact Current Rating (A)	1
	Contact Base Material	Brass
	Contact Type	Pin
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness	.76 μm [30 μin]
	Contact Shape	Square
	Solder Tail Contact Plating Material	Tin
	Contact Termination Area Plating Material	Tin
	Contact Termination Area Plating Thickness	2.54 μm [100 μin]

Termination Features	Termination Method to PC Board	Through Hole
	Termination Post Length	2.79 mm [.11 in]

Mechanical Attachment	PCB Mount Retention	Without
	Mating Alignment Type	Center, Dual Polarizing Bar
	Mating Connector Lock	With
	Mating Connector Lock Type	Latch
	Mating Alignment	With
	Polarization	With
	Panel Mount Retention	Without
	Mating Retention	With
PCB Mount Alignment	Without	

Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Style	4-Sided
	Housing Material	Glass Filled Nylon/Polyester

Dimensions	Shrouded End Dimension	3.81 mm [.15 in]
	Length	62.48 mm [2.46 in]
	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Height	13.94 mm [.548 in]

Usage Conditions	Temperature Rating	Standard
	Operating Temperature Range (°C)	-65 – 105

Operation/Application	For Use With	Mates with Receptacles
-----------------------	--------------	-------------------------------

Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------





Packaging Features	Packaging Method	Tray
	Packaging Quantity	24

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES</p>  <p>6P AMPMODU II STIFT LEI 826631-6</p> <p>Save to List Find Similar Products</p>	<p>BOARD-TO-BOARD HEADERS & RECEPTACLES</p>  <p>FB-5R, ASY, 030, SIG, HDR, EN, 4.25 5223002-1</p> <p>Save to List Find Similar Products</p>	<p>PCB D-SUB CONNECTORS</p>  <p>09 RCPT SP/MS STD 5745183-3</p> <p>Save to List Find Similar Products</p>	<p>RIBBON CABLE CONNECTORS</p>  <p>010 UNIV HDR SP 4S 30DP STD L1 499206-1</p> <p>Save to List Find Similar Products</p>
--	---	---	--

Products - 11 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼


RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Ribbon Cable Connectors AMP-LATCH AMP-LATCH - NOVO</p> <p>34 NOVO MIL 30DP, LEAD FREE - 1658623-8</p> <p>TE INTERNAL NUMBER: 1658623-8</p> <p>✓ Active</p> <p>Always EU RoHS/ELV Compliant</p> <p>Centerline 2.54 mm</p> <p>PCB Mount Retention Without</p> <p>PCB Mounting Orientation Vertical</p> <p>Termination Method to PC Board Through Hole - Solder</p> <p>Termination Method to Wire/Cable Insulation Displacement Crimp (IDC)</p>
---	---


	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Ribbon Connector Accessories AMP-LATCH AMP-LATCH - NOVO</p> <p>034 STRAIN RELIEF A-L RCPT - 499252-6</p> <p>TE INTERNAL NUMBER: 499252-6 ALIAS ID: 1108436, 2-42933-5038</p> <p>✓ Active</p> <p>Always EU RoHS/ELV Compliant</p> <p>Accessory Type Strain Relief</p>
---	---


RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Ribbon Connector Accessories AMP-LATCH AMP-LATCH - NOVO</p> <p>034 STRAIN RELIEF A-L</p> <p>Accessory Type Strain Relief</p>
---	---



RCPT - 499252-6

TE INTERNAL NUMBER: 499252-6
ALIAS ID: 1108436, 2-42933-5038

✓ Active

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
AMP-LATCH | AMP-LATCH - NOVO

034 NOVO DUAL 30DP

FT - 1658624-8

TE INTERNAL NUMBER: 1658624-8

✓ Active

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation

Vertical

Termination Method to PC Board

Through Hole - Solder

Termination Method to

Wire/Cable **Insulation**

Displacement Crimp (IDC)




RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Connector Accessories
AMP-LATCH | AMP-LATCH - NOVO

609-3431HD=FSKT IDC S

34 SR - 3-1437021-2

TE INTERNAL NUMBER: 3-1437021-2
ALIAS ID: 609-3431HD

✓ Active


Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**

Number of Positions **34**



PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
AMP-LATCH - NOVO

609-3430LF FEM SOCKT,

LEAD FREE - 1-1658526-8

TE INTERNAL NUMBER: 1-1658526-8

✓ Active

Always EU RoHS/ELV Compliant

Number of Positions **34**

Connector Style **Receptacle**

