


5650478-5 Product Details

[Share](#) [Print](#) [Email](#)




5650478-5

TE Internal Number: 5650478-5

 Active

[View 3D PDF](#)

Eurocard Type C

 Always EU RoHS/ELV Compliant
(Statement of Compliance)

Product Highlights:

- Eurocard Product Line
- Product Series = Type C
- Connector Assembly
- Connector Style = Plug
- Board-to-Board

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)

[Request Sample](#)

[Find Similar Products](#)

[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [ASSEMBLY, PIN, EUROCARD, TYPE 1/2C, 48 POSITION, 2.6...](#) (PDF, English)
- [ASSEMBLY, PIN EUROCARD, TYPE C, .104 SOLDER POST](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- [Eurocard Connectors Types B,C,M,Q,R, & Enhanced Typ...](#) (PDF, English)

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing](#) (DXF, Version 0)
- [3D Model](#) (IGES, Version 0)
- [3D Model](#) (STEP, Version 0)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Line = Eurocard
- Product Series = Type C
- Connector Type = Connector Assembly
- [PCB Mount Retention](#) = Without
- [PCB Mounting Orientation](#) = Right Angle
- Size = Half
- [Make First / Break Last](#) = No
- [DIN Level](#) = II

Electrical Characteristics:

- Contact - Rated Current (A) = 1.5

Termination Features:

- [Termination Post Length \(mm \[in\]\)](#) = 2.65 [0.104]

Configuration Features:

- Number of Rows = 3
- [Number of Positions](#) = 48
- [Rows Loaded](#) = A, B, C

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- [RoHS/ELV Compliance History](#) = Always was RoHS compliant

Conditions for Usage:

- [Applies To](#) = Printed Circuit Board

- Termination Method to PC Board = Through Hole - Solder

Contact Features:

- Contact Type = Pin
- Contact Base Material = Brass
- Contact Cross Section (mm [in]) = 0.64 [.025] Sq.

Housing Features:

- Connector Style = Plug
- Centerline (mm [in]) = 2.54 [0.100]
- Mating Alignment = With
- Mating Alignment Type = Polarization
- Housing Material = Glass Filled Polyester
- UL Flammability Rating = UL 94V-0

Operation/Application:

- Application Use = Board-to-Board
- Contact Transmits (Typical Application) = Signal (Data)

Other:

- Brand = AMP

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



