


Product Details for 6339191 - 4



PCB Mounted Jacks - Single Port, Multi - port and Stacked

[RoHS Compliant](#) (Statement of Compliance)

Product Highlights:

- ? Jack
- ? Single Port Configuration
- ? 1 x 1 Jack Configuration
- ? Jack Type = RJ45
- ? Number of Positions = 8

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

6339191 - 4

[Active](#)

Documentation & Additional Information

Product Drawings:

- ? [INVERTED MODULAR JACK ASSEMBLY, 1x1, SHIELDED, SURFA...](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? [Inverted Six and Eight Position Surface Mount Shield...](#) (PDF, English)

Application Specifications:

- ? [Modular Jacks with Integral Light Emitting Diode \(LED\)](#) (PDF, English)
- ? [Modular Jack Surface Mount PC \(Printed Circuit\) Boar...](#) (PDF, English)

Instruction Sheets:

- ? None Available

CAD Files: ([CAD Format & Compression Information](#))

- ? [3D Model](#) (STEP, Version B)
- ? [3D Model](#) (IGES, Version B)
- ? [2D Drawing](#) (DXF, Version B)

[List all Documents](#)

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Product Type](#) = Jack
- ? [Jack Type](#) = RJ45
- ? [Number of Positions](#) = 8
- ? [PCB Mount Angle](#) = Side Entry (Right Angle)
- ? [PCB Mount Style](#) = Surface Mount
- ? [PCB Termination Type](#) = Solder
- ? [Shielded](#) = Yes
- ? [Performance Category](#) = Cat 3
- ? Number of Contacts Loaded = 8
- ? Grounding Options = Without
- ? [Panel Stops](#) = Without
- ? [Keyed](#) = No
- ? [Profile](#) = Standard
- ? IR Reflow Compatible = Yes
- ? [Color](#) = Black
- ? Shield Material = Copper Alloy
- ? PCB Thickness (mm [in]) = 1.57 [0.062]

Mechanical Attachment:

- ? [Jack Configuration](#) = 1 x 1
- ? [Panel Attachment](#) = With
- ? Flanged = No

Termination Related Features:

- ? [Height \(mm \[in\]\)](#) = 13.34 [0.525]
- ? [Solder Tail Plating](#) = Tin over Nickel

Body Related Features:

- ? Port Configuration = Single
- ? [Inverted Jack Face](#) = Yes
- ? [LED](#) = With
- ? Shield Plating = Tin
- ? PCB Ground Tab Location (mm [in]) = 0.00 [0.000]

Contact Related Features:

- ? [Contact Mating Area Plating](#) = Gold (50) over Nickel (50)
- ? Contact Material = Phosphor Bronze

Housing Related Features:

- ? Housing Material = High Temperature Thermoplastic
- ? Housing Flammability Rating = UL 94V -0

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Reflow solder capable to 245°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Identification Marking:

- ? [LED Position 1 Color](#) = Yellow
- ? [LED Position 2 Color](#) = Green
- ? [LED Position 3 Color](#) = None

Packaging Related Features:

- ? Panel Ground Location = Top and Side
- ? Packaging Method = Tape Mounted on Reel
- ? Packaging Quantity = 200 Pieces (per 38 cm diameter reel)

Other:

- ? Brand = AMP