

HARD METRIC BACKPLANE CONNECTORS



✓ Active

PRODUCT DRAWING
English
3D PDF

TE CONNECTIVITY (TE) HMZD 3PAIR, HDR ASSY, 25MM MOD Z-PACK | HM-Zd

6469083-1 TE Internal Number: 6469083-1

Always EU RoHS/ELV Compliant

Data Rate (Gb/s) **≤12**

Number of Columns 10

Number of Rows **6**

Number of Pairs **30**

Centerline (mm) 2.5

Product Drawings	HEADER ASSEMBLY, 3 PAIR, 2.5mm TAIL, 25mm, HMZd PDF English			
CAD Files	Customer View Model 2D_DXF.ZIP English			
	3D PDF PDF 3D			
	Customer View Model 3D_IGS.ZIP English			
	Customer View Model 3D_STP.ZIP English			
Catalog Pages/Data Sheets	High Speed Backplane Connectors Catalog - Z-PACK HM-Zd Connector PDF English			
Product Specifications				
Product Specification	Two, Three And Four Pair HM-Zd Connectors PDF English			
Application Specification	Z-PACK Hard Metric (HM)-Zd And HM-Zd Plus 2-, 3-, And 4-Pair Connector Systems PDF			
Qualification Test Report	English Two, Three And Four Pair HM-Zd Connectors PDF English			

Product Environmental Compliance

TE Material Declaration

MD_6469083-1_01212014739_dmtec PDF English 9 6 f v

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Vertical	
	Connector Type	Header	
	Applies To	Printed Circuit Board	
	Shielded	Yes	
	Connector Style	Plug	
	Make First / Break Last	Νο	
Configuration Features	Number of Columns	10	
	Number of Rows	6	
	Number of Pairs	30	
	Number of Positions	60	
	Pairs per Column	3	
	Sequenced Pins	No	
	Selectively Loaded	Νο	
Signal Characteristics	Data Rate (Gb/s)	≤12	
Body Features	Shield Material	Phosphor Bronze	
Contact Features	Contact Mating Area Plating Material	Gold	
	Contact Mating Area Plating Thickness (µm)	.76	
	Contact Mating Area Length (mm)	5.3	
	CompactPCI Designation	None	
	Feedthrough Post Length (mm)	2.5	
	Contact Base Material	Phosphor Bronze	
	Contact Configuration	Compliant Pin	
	Grounding Contact	With	
	Contact Type	Pin	
Termination Features	Termination Method	Press-Fit	
	Contact Termination Type	Through Hole	
	Termination End Plating Material	Tin over Nickel	
		HM-Zd	
	Interface Type	nw-20	

Mechanical Attachment	Mating Alignment Type	Polarization	
Housing Features	Centerline (mm)	2.5	
	Housing Color	Gray	
	Housing Material	Polyester - GF	
Dimensions	Card Slot Centerline (mm)	20.3	
	Module Length (mm)	24.9	
Industry Standards	UL Flammability Rating	UL 94V-0	
	AdvancedTCA Specified Product	Νο	
Packaging Features	Packaging Method	Tube	
	Packaging Quantity	20	
Product Compliance	Statement of Compliance PDF		

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

HARD METRIC BACKPLANE CONNECTORS	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES	HARD METRIC BACKPLANE CONNECTORS	RECTANGULAR POWER CONNECTORS	
Control Sector			Prop.	
Z-PACK/A M HDR.154P 5188578-1	03 MODII HDR SRST UNSHRD A/PIN 4-102898-0	HMZD 3PR, RECEPTACLE ASSEMBLY 6469081-1	UNV PWR MDL ASY RECEPT 5223955-2	>
Save to List	Save to List	Save to List	📒 Save to List	
Find Similar Products	Find Similar Products	Find Similar Products	Find Similar Products	



See All Mating Products



RELATIONSHIP **Mating Products** Used to identify Mating Parts



PRODUCT - MATING PRODUCTS

Connectors - Hard Metric Connectors Z-PACK I HM-Zd HMZD 3PR, RECEPTACLE

ASSEMBLY - 6469081-1 TE INTERNAL NUMBER: 6469081-1

✓ Active

Always EU RoHS/ELV Compliant

Data Rate **≤12 Gb/s**

Number of Columns 10

Number of Rows **6**

Number of Pairs **30**

Centerline **2.5 mm**