



a vital part of your world

Find Answers:

Thursday, 17 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Multimate Contacts

↳ Multimate

AMP 66361-2 Active

[Not ELV or RoHS Compliant](#)

(Corporate P/N: 66361-2)

[Search for Compliant \(RoHS/ELV\)](#)

[Alternates](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ➤ General Info ➤ Sales Info ➤ Assembly Subcontractors 	<ul style="list-style-type: none"> ➤ Pricing & Availability 	<ul style="list-style-type: none"> ➤ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

[Line Drawing](#)

Searchable Features:		Other Properties:	
Brand:	AMP	Pin Diameter (mm [in]):	1.57 [0.062]
RoHS/ELV Compliance:	Not ELV/RoHS compliant	Wire/Cable Type:	Discrete Wire
Lead Free Solder Processes:	Not relevant for lead free process	Test Current (Amps.):	13.0
Pin/Socket:	Pin	Spring Material:	Stainless Steel
High Current:	No	Grade:	Commercial
Contact Mating Area Plating:	Bright Tin-Lead	Used With:	G Series Connectors, M Series Connectors, CPC Connectors
Wire Range (mm [AWG]):	0.8-2.0mm ² [18-14]		
Insulation Diameter (mm [in]):	2.03 – 2.54 [0.080 – 0.100]		
Contact Material:	Brass		

<u>Termination End Plating:</u>	Bright Tin-Lead
Product Type:	Type III+
<u>Contact Size:</u>	16
<u>Contact Type:</u>	Signal
<u>Terminate To:</u>	Wire
<u>Insulation Support:</u>	Yes
<u>Wire Termination Type:</u>	Crimp
<u>Packaging Method:</u>	Loose Piece

Comment:	Overall insulation crimp diameter, including crimp barrel, must not exceed 3.18 [.125]. Insertion Tool No. 91002-1 (for Insulation Dia. 1.78 [.070] or less), No. 200893-2 (for Insulation Dia. .090 [2.29] max.) Extraction Tool No. 305183.
-----------------	---

[Copyright and Privacy Statement](#)
 Visit [Tyco International Ltd.](#)

[\[Products | Catalog | Brands | Industries | Commerce | Supplier | Contact Us | About | Home \]](#)