

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION, 19 .
 © COPYRIGHT 19 BY AMP INCORPORATED. ALL INTERNATIONAL RIGHTS RESERVED.

LOC	DIST	P	F	ZONE	LTR	REVISIONS	DATE	APPD
GP	00				A	REVISED PER EC 0513-0160-03	22MAY03	JG

CABLE SUPPLIED BY CUSTOMER

32.77
[1.290]

33.91
[1.335]

10.16
[.400]

STRAIN RELIEF STAPLE (1 SUPPLIED)
MATERIAL: STEEL
FINISH: SEE TABLE

SPRING LATCH (2 SUPPLIED)
MATERIAL: STAINLESS STEEL

MACHINE SCREW (2 SUPPLIED)
#2-56 UNC X.250

CONNECTOR (MUST BE PURCHASED SEPARATELY)

UPPER BACKSHELL (1 SUPPLIED)
MATERIAL: ZINC PLATING: NICKEL OVER COPPER

LOWER BACKSHELL (1 SUPPLIED)
MATERIAL: ZINC PLATING: NICKEL OVER COPPER

- ① .270 MAX CABLE DIA
- 2. DIMENSIONS IN BRACKETS ARE IN INCHES.
- ③ BRIGHT TIN-LEAD OVER NICKEL.
- ④ BRIGHT TIN OVER NICKEL.



④	749608-2
③	749608-1
STAPLE FINISH	PART NO

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN INCHES- MM TOLERANCES ON:	DR 05/08/89 M.MCCAFFREY
2 PLC DEC ± -	CHK 05/11/89 M.E.SHIRK
3 PLC DEC ± 0.38 [.015]	APPD 05/23/89 J.BROSCHARD
ANGLES ± -	APPD -
MATERIAL -	PRODUCT SPEC -
FINISH -	APPLICATION SPEC -
	WEIGHT -

AMP		AMP INCORPORATED Harrisburg, Pa. 17105
NAME INDIVIDUAL KIT, 26 POSITION, REDUCED WIDTH, STRAIGHT EXIT, UNKEYED, AMPLIMITE .050 Series		
SIZE B	FSCM NO 00779	DRAWING NO 749608
SCALE 2:1	SHEET 1 OF 1	