


## 794132-1 Product Details



**794132-1**

TE Internal Number: 794132-1



Active

 [View 3D PDF](#)

**.200" Centerline, 250 V, 13 A max.**

 [Always EU RoHS/ELV Compliant](#)  
([Statement of Compliance](#))

**Product Highlights:**

- Housing
- Housing Type = Receptacle (Cap)
- Housing Accepts Contact Type = Socket
- In-Line Contact Layout
- 5.08 mm Centerline

[View all Features](#)

### Documentation & Additional Information

**Product Drawings:**

- [TM](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- [SOFT SHELL PIN SOCKET CONNECTORS STANDARD DENSITY](#) (PDF, English)

**Product Specifications:**

- None Available

**Application Specifications:**

- [MATE-N-LOK Commercial Pin And Socket Contacts](#) (PDF, English)

**Instruction Sheets:**

- None Available

**CAD Files:** ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version 0)
- [3D Model](#) (IGES, Version 0)
- [3D Model](#) (STEP, Version 0)

[List all Documents](#)

**Additional Information:**

- [Product Line Information](#)

**Related Products:**

- [Tooling](#)
- [Mating Products \(1\)](#)
- [Contacts \(146\)](#)

### Product Features (Please use the Product Drawing for all design activity)

**Product Type Features:**

- Product Type = Housing
- Mount = Free Hanging or Panel
- Number of Positions = 4
- Product Line = Commercial MATE-N-LOK
- Comment = Housing accepts double wire applications where individual insulation diameters do not exceed 2.92 [.115 ]; Used by the disk drive industry.

**Mechanical Attachment:**

- Mating Retention = With
- Mating Retention Type = Detent Lock

**Electrical Characteristics:**

- Voltage (VAC) = 250
- Current Rating (Amps.) = 13

**Contact Related Features:**

- Housing Accepts Contact Type = Socket
- Contact Layout = In-Line

**Housing Related Features:**

- Housing Type = Receptacle (Cap)
- Housing Material = Nylon
- Housing Color = Natural
- Housing Flammability Rating = UL 94V-0

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

**Body Related Features:**

- Centerline (mm [in]) = 5.08 [0.200]
- Contact Diameter (mm [in]) = 2.13 [0.084]

**Other:**

- Brand = AMP