




Have a Question?
 Chat with a Product Information Specialist

What can we help you find?

[Products](#) |
 [Industries](#) |
 [Resources](#) |
 [About TE](#) |
 [My Account](#) |
 [Innovation](#) |
 [Support Center](#)

794280-1 Product Details

[Share](#) |
 [Print](#) |
 [Email](#)



794280-1

TE Internal Number: 794280-1

Active

[View 3D PDF](#)

.250" Centerline, 600 V, 19 - 36 A max

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Universal MATE-N-LOK Product Line
- Wire-to-Wire
- Accessory
- Accessory Type = Wire Seal
- Glow Wire Rating = Standard Part - Not Glow Wire

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) |
 [Request Sample](#) |
 [Find Similar Products](#) |
 [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • WIRE SEAL,12 CIRCUIT, (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • 2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1 (PDF, English) • SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • MATE-N-LOK Sealed Universal Connectors (PDF, English) <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • Universal MATE-N-LOK Splash Proof Seals (PDF, English) <p>CAD Files: (CAD Format & Compression Information)</p> <ul style="list-style-type: none"> • 2D Drawing (DXF, Version A) • 3D Model (IGES, Version A) • 3D Model (STEP, Version A) 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Additional Product Images:</p> <ul style="list-style-type: none"> • Schematic <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Line = Universal MATE-N-LOK • Product Type = Accessory • Accessory Type = Wire Seal • Accessory Color = Blue • Sealed = No • Wire/Cable Type = Discrete Wire <p>Termination Features:</p> <ul style="list-style-type: none"> • Wire/Cable Size (mm²) = 0.5 - 2 • Wire/Cable Size (AWG) = 14 - 20 <p>Body Features:</p> <ul style="list-style-type: none"> • Wire Type = Stranded • Row-to-Row Spacing (mm [in]) = 6.35 [0.250] <p>Contact Features:</p> <ul style="list-style-type: none"> • Contact Layout = Matrix • Multiple Contact Types = Without <p>Housing Features:</p> <ul style="list-style-type: none"> • Centerline (mm [in]) = 6.35 [0.2499] • Housing Material = Silicone 	<p>Configuration Features:</p> <ul style="list-style-type: none"> • Number of Positions = 12 <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Always was RoHS compliant <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Glow Wire Rating = Standard Part - Not Glow Wire • Accepts Wire Insulation Diameter, Range (mm [in]) = 1.52 - 3.30 [0.060 - 0.130] • For Use With = Universal MATE-N-LOK Sealed Connectors <p>Operation/Application:</p> <ul style="list-style-type: none"> • Application Use = Wire-to-Wire <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Bag • Packaging Quantity = 400 <p>Other:</p> <ul style="list-style-type: none"> • Brand = AMP

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
CM	53	P	LTR	DESCRIPTION	DATE	DWN	APVD
		C		REVISED PER ECR-12-011218	08OCT12	KH	TM

1 MATERIAL: SELF LUBRICATING SILICON RUBBER
 COLOR: BLUE

2 DIMENSIONS IN BRACKETS ARE IN INCHES.

20.32
[.800]

26.67
[1.050]

3-DIMENSIONAL MODEL
 NTS

794279-1
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	B. LEWIS	3-25-97		TE Connectivity			
DIMENSIONS:		CHK	R. SWING	3-25-97		NAME			
mm [INCHES]		APVD	D. SELF	3-25-97		INTERFACE SEAL, 12 CIRCUIT, UNIVERSAL MATE-N-LOK™			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	APPLICATION SPEC			SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
0 PLC	± -	WEIGHT		-	A2	00779	C=794279	-	
1 PLC	± -	CUSTOMER DRAWING			SCALE	4:1	SHEET	1 of 1	REV
2 PLC	± 0.38[.015]								C
3 PLC	± -								
4 PLC	± -								
ANGLES	± 0°30'								
MATERIAL	FINISH								
1	-								

1471-9 (3/11)

794279

B

A