




CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
German

↓ **3D PDF**

TE CONNECTIVITY (TE)

55P JUN-TIM GEH MIX

AMP | Junior Timer , Timer Connector System

828761-1

TE Internal Number: 828761-1

Always EU RoHS/ELV Compliant

Connector Style **Housing for male terminals**

Mating Tab Width (mm) **1.6, 3**

Mating Tab Width (in) **.063, .118**

Number of Positions **55**

Pitch (mm) **3, 5**

Pitch (in) **.118, .197**

Sealed **Yes**

Product Drawings

[55 Pol Stecker Fur 8 Junior Timer Und 47 Micro Timer Kontakt](#)

PDF (TIFF AVAILABLE)

German

[55 Pol Stecker Fur 8 Junior Timer Und 47 Micro Timer Kontakt](#)

PDF (TIFF AVAILABLE)

German

CAD Files

[Customer View Model](#)

3D_IGS.ZIP

English

[Customer View Model](#)

3D_STP.ZIP

English

[Customer View Model](#)

2D_DXF.ZIP

English

[3D PDF](#)

PDF

English

Product Specifications

Product Specification

[CONNECTEUR JUNIOR TIMER 828761-1 EQUIPE DE CONTACTS JPT ET MT](#)

TIF

English

[CONNECTEUR JUNIOR TIMER 828761-1 EQUIPE DE CONTACTS JPT ET MT](#)

PDF

English

[Packaging Instruction](#)

PDF

English

Product Type Features	Connector Style	Housing for male terminals
	Sealed	Yes
	Hybrid Connector	Yes
	Primary Locking Feature	On the terminal
	Connector System	Wire-to-Board/Device
	Row-to-Row Spacing	5 mm [.197 in]
	Strain Relief	Yes
Configuration Features	Number of Positions	55
	Number of Rows	2
Body Features	Cable Exit Angle	90°
	Body Material	PBT GF
	Color	Black
Contact Features	Mating Tab Width (mm)	1.6, 3
	Mating Tab Width (in)	.063, .118
Mechanical Attachment	Terminal Position Assurance	No
	Mounting Feature	No
	Polarized	No
Housing Features	Pitch (mm)	3, 5
	Pitch (in)	.118, .197
Dimensions	Width	39 mm [1.535 in]
	Height	29 mm [1.142 in]
	Length	149.5 mm [5.886 in]
Usage Conditions	Operating Temperature (Max) (°C)	70, 75, 80, 85, 90, 100
	Operating Temperature (Max) (°F)	158, 167, 176, 185, 194, 212
	Operating Temperature Range	-40 – 100 °C [-40 – 212 °F]
Industry Standards	Degree of Protection	Other
	UL Flammability Rating	UL 94-HB

Packaging Features

Packaging Method

Box

Other

Connector Position Assurance Capable

No

Serviceable





No

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HEADERS</p>  <p>55P MESSER LEI MIX 828763-1</p> <p>Save to List Find Similar Products</p>	<p>CRIMP QUICK DISCONNECTS</p>  <p>FF FLACHST MIF 6, 3 160869-2</p> <p>Save to List Find Similar Products</p>	<p>AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD TERMINALS</p>  <p>MICRO TIMER CONTACT 929952-1</p> <p>Save to List Find Similar Products</p>	<p>PRO-CRIMPER & DIES</p>  <p>ASSY PRO-CRIMPER UNIV M-N-L 90546-1</p> <p>Save to List Find Similar Products</p>
--	--	---	--

Products - 1 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Automotive, Truck, Bus, & Off-Road Headers

AMP | Timer Connector System

55P MESSER LEI MIX

- 828763-1

TE INTERNAL NUMBER: 828763-1

✓ Active

Always EU RoHS/ELV Compliant

Tab Width **1.6 mm, 3 mm**

Tab Thickness **.8 mm**

Pitch **3 mm, 5 mm**

Number of Circuits **55**

Sealed **No**