



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

CONTENTS

Section 1	INTRODUCTION	
Section 2	BLACK 1966-RIBBONS, 2000P-4TT, T300-RIBBON-UV-SCE	THERMAL TRANSFER RIBBONS
Section 3	BLACK TMS	THERMAL TRANSFER RIBBONS
Section 4	BLACK TTB	THERMAL TRANSFER RIBBONS
Section 5	BLACK 1330	THERMAL TRANSFER RIBBONS
Section 6	WHITE & SILVER	THERMAL TRANSFER RIBBONS
Section 7	BTT-02 CARD PRINTER	THERMAL TRANSFER RIBBONS
Section 8	DOT MATRIX	INK CARTRIDGES

Section 1

Introduction	The "Identification Printer Product Ribbon Matrix" (TE document number 411-121005), must be consulted in conjunction with this document. This document supersedes all previous Thermal Transfer ribbon and ink technical data sheets.
---------------------	--

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 1 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 2 BLACK 1966-RIBBONS, 2000P-4TT, T300-RIBBON-UV-SCE THERMAL TRANSFER RIBBONS

Ribbon Description	Part number	Shelf life and storage conditions	Ribbon Length	Ribbon Width	Core Inside Diameter	Winding direction	Colour
1966-RIBBON	F55931-000	1 year, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	100mm (3.9 inches)	25.4mm (1 inch)	Ink side out	Black
LBF-2000P-RIBBON-1966-MED	6-1768383-4	1 year, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	60mm (2.36 inches)	25.4mm (1 inch)	Ink side out	Black
T200-RIBBON-1966	D60849-000	1 year, when stored between -5°C (23°F) and 40° (104°F)	74m (242 feet)	110mm (4.3 inches)	12.7mm (1/2 inch)	Ink side out	Black
2000P-RIBBON-4TT-MED	893803-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	60mm (2.36 inches)	25.4mm (1 inch)	Ink side out	Black
2000P-RIBBON-4TT-NAR	277493-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	40mm (1.57 inches)	25.4mm (1 inch)	Ink side out	Black
T300-UV-SCE-RIBBON	EC8932-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	Black

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 2 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 3 BLACK TMS THERMAL TRANSFER RIBBONS

Ribbon Description	Part number	Shelf life and storage conditions	Ribbon Length	Ribbon Width	Core Inside Diameter	Winding direction	Colour
TMS-RJS-RIBBON-4DSCE	311292-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	450m (1476 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	Black
TMS-101-RIBBON-4DSCE	505478-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	Black
TMS-RJS-RIBBON-4RPSCE	557721-000	3 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	Black
TMS-101-RIBBON-4RPSCE	310109-000	3 years, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	Black
TMS-RJS-RIBBON-4HT	754073-000	3 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	Black
TMS-101-RIBBON-4HT	746617-000	3 years, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	Black

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 3 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 4 BLACK TTB THERMAL TRANSFER RIBBONS

Ribbon Description	Part number	Shelf life and storage conditions	Ribbon Length	Ribbon Width	Core Inside Diameter	Winding direction	Colour
TTB-060SC/300	2-1768049-6	1 year, when stored between 5 (40°F) and 35°C (95°F)	300m (984 feet)	60mm (2.36 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-076SC/300	3-1768049-0	1 year, when stored between 5 (40°F) and 35°C (95°F)	300m (984 feet)	76mm (3 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-084SC/300	C75514-000	1 year, when stored between 5 (40°F) and 35°C (95°F)	300m (984 feet)	84mm (3.3 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-110SC/300	3-1768049-6	1 year, when stored between 5 (40°F) and 35°C (95°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-114SC/300	3-1768049-6	1 year, when stored between 5 (40°F) and 35°C (95°F)	300m (984 feet)	114mm (4.48 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-128SC/450	4-1768049-1	1 year, when stored between 5 (40°F) and 35°C (95°F)	450m (1476 feet)	128mm (5.04 inches)	25.4mm (1 inch)	Ink side out	Black

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 4 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 4 BLACK TTB THERMAL TRANSFER RIBBONS (Continued)

Ribbon Description	Part number	Shelf life and storage conditions	Ribbon Length	Ribbon Width	Core Inside Diameter	Winding direction	Colour
TTB-145SC/450	4-1768049-3	1 year, when stored between 5 (40°F) and 35°C (95°F)	450m (1476 feet)	145mm (5.70 inches)	25.4mm (1 inch)	Ink side out	Black
TTB-170SC/450	4-1768049-1	1 year, when stored between 5 (40°F) and 35°C (95°F)	450m (1476 feet)	170mm (6.70 inches)	25.4mm (1 inch)	Ink side out	Black
TTB-076SC/300WH	3-1768049-1	1 year, when stored between 5 (40°F) and 35°C (95°F)	300m (984 feet)	76mm (3 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-084SC/300WH	3-1768049-3	1 year, when stored between 5 (40°F) and 35°C (95°F)	300m (984 feet)	84mm (3.3 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-110SC/300WH	3-1768049-8	1 year, when stored between 5 (40°F) and 35°C (95°F)	300m (984 feet)	110mm (4.30 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-145SC/300WH	3-1768049-1	1 year, when stored between 5 (40°F) and 35°C (95°F)	300m (984 feet)	145mm (5.70 inches)	25.4mm (1 inch)	Ink side in	Black

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 5 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 4 BLACK TTB THERMAL TRANSFER RIBBONS (Continued)

Ribbon Description	Part number	Shelf life and storage conditions	Ribbon Length	Ribbon Width	Core Inside Diameter	Winding direction	Colour
TTB-170SC/450WH	4-1768049-8	1 year, when stored between 5°C (40°F) and 35°C (95°F)	450m (1476 feet)	170mm (6.70 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-060SC/450AQ529	2-1768049-7	1 year, when stored between 5°C (40°F) and 35°C (95°F)	450m (1476 feet)	60mm (2.36 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-090SC/360-AQ529	3-1768049-4	1 year, when stored between 5°C (40°F) and 35°C (95°F)	360m (1181 feet)	90mm (3.54 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-110SC/300AQ529	3-1768049-7	1 year, when stored between 5°C (40°F) and 35°C (95°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side in	Black
TTB-114SC/360AQ529	4-17680409-3	1 year, when stored between 5°C (40°F) and 35°C (95°F)	300m (984 feet)	114mm (4.48 inches)	25.4mm (1 inch)	Ink side out	Black
TTB-166SC/360AQ529	8-1768402-6	1 year, when stored between 5°C (40°F) and 35°C (95°F)	360m (1181 feet)	166mm (6.53 inches)	25.4mm (1 inch)	Ink side out	Black

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 6 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 5 BLACK 1330 THERMAL TRANSFER RIBBONS

Ribbon Description	Part number	Shelf life and storage conditions	Ribbon Length	Ribbon Width	Core Inside Diameter	Winding direction	Colour
1330-0600-10	143060-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	Black
1330-0600-T200	C36369-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	Black
1330-TTB-T200	1-1768384-8	1 year, when stored between 5°C (40°F) and 35°C (95°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	Black
1330-3300-10	980892-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.3 inches)	25.4mm (1 inch)	Ink side out	Black
1330-3300-101TT	C95590-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.3 inches)	12.7mm (1/2 inch)	Ink side out	Black
1330-0607-10	742412-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	Black

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 7 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 5 BLACK 1330 THERMAL TRANSFER RIBBONS (Continued)

Ribbon Description	Part number	Shelf life and storage conditions	Ribbon Length	Ribbon Width	Core Inside Diameter	Winding direction	Colour
1330-0607-T200	E45478-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	Black
1330-0619-10	952888-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	Black
1330-0619-T200	C49013-000	2 years, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	Black

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 8 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 6 WHITE and SILVER THERMAL TRANSFER RIBBONS

Ribbon Description	Part number	Shelf life and storage conditions	Ribbon Length	Ribbon Width	Core Inside Diameter	Winding direction	Colour
T300-RIBBON-WH-4HT	154739-000	3 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	White
T200-RIBBON-WH-4HT	086961-000	3 years, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	White
T300-RIBBON-WH	650784-000	1 year, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	White
T200-RIBBON-WH	117366-000	1 year, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	White
TMS-RJS-RIBBON-4AG	124503-000	3 years, when stored between -5°C (23°F) and 40°C (104°F)	300m (984 feet)	110mm (4.33 inches)	25.4mm (1 inch)	Ink side out	Silver
TMS-101-RIBBON-4AG	252557-000	3 years, when stored between -5°C (23°F) and 40°C (104°F)	74m (242 feet)	110mm (4.33 inches)	12.7mm (1/2 inch)	Ink side out	Silver

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 9 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 7 BTT-02 CARD PRINTER THERMAL TRANSFER RIBBONS

Ribbon Description	Part number	Shelf life and storage conditions	Ribbon Length	Ribbon Width	Core Inside Diameter	Winding direction	Colour
BBB-060BL/200	1-1768016-1	2 years, when stored between -5°C (23°F) and 40°C (104°F)	200m (656 feet)	60mm (2.36 inches)	12.7mm (1/2 inch)	Ink side out	Blue
BBB-060RT/200	1-1768016-3	2 years, when stored between -5°C (23°F) and 40°C (104°F)	200m (656 feet)	60mm (2.36 inches)	12.7mm (1/2 inch)	Ink side out	Red
BBB-060SC/200	1-1768016-4	2 years, when stored between -5°C (23°F) and 40°C (104°F)	200m (656 feet)	60mm (2.36 inches)	12.7mm (1/2 inch)	Ink side out	Black
BBB-060WE/200	1-1768016-5	2 years, when stored between -5°C (23°F) and 40°C (104°F)	200m (656 feet)	60mm (2.36 inches)	12.7mm (1/2 inch)	Ink side out	White

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 10 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 8 DOT MATRIX INK CARTRIDGES

Ribbon Description	Part number	Shelf life and storage conditions	Colour
LQ590-RIBBON	1-2186029-1	6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging.	Black
TMS-SYSTEM-SIX-RIBBON-A	310347-000	6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging.	Black
TMS-LQ590-RIBBON	CC3130-000	6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging.	Black
TMS-SYSTEM-SIX-RIBBON-B	264327-000	6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging.	Black
1892BK04-RIBBON	D06106-000	6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging.	Black
1892BK03-HIGH-PERF-RIBBON	A72722-000	6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging.	Black

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 11 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



TECHNICAL DATA SHEET

Printing Ribbons and Inks

Document number: TTDS-257
Issue: 2
Date: January 2014

Section 8 DOT MATRIX INK CARTRIDGES (Continued)

Ribbon Description	Part number	Shelf life and storage conditions	Colour
18910000-OKI380-RIBBON	856832-000	6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging.	Black
1330-0037-00	9-1198202-3	6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging.	Black

If the document is printed it becomes uncontrolled
Check with TE Connectivity (TE) for latest version

Author: Ian Ridgeway
Issue date: January 2014
Page: 12 of 12

While TE Connectivity Ltd. has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.