



- 1 COPPER ALLOY PER ASTM B301
- 2 1.27 μm [50 μin] MIN GOLD PER ASTM B488
OVER 2.54 μm [100 μin] MIN NICKEL PER
QQ-N-290 ON ENTIRE STOCK.
- 3. APPLICATION TOOLING:
CRIMPING TOOL: M22520/23-01
DIE SET: M22520/23-02
LOCATOR: TYCO P/N 1738331-1
EXTRACTION TOOL: M81969/28-01
- 4. WIRE ACCOMMODATED: 8 AWG
STRIP LENGTH: 9.60 [.378] - 10.10 [.398]
- 5. THIS PRODUCT IS SOLD BY TYCO ELECTRONICS
UNDER A LICENSE FROM RADIAL SA

PRELIMINARY
NOT RELEASED FOR
PRODUCTION

DIMENSIONS : mm [inch]

Tyco PN - 1738019-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		CHK	22MAR2004	Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS: mm [INCHES]		APPROVED	DATE	POWER CONTACT, PIN, CRIMP TERMINATION SIZE 5 GPR	
DIMENSIONS UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	APPLICATION SPEC	SIZE	DATE CODE
0 P.L.C.	± .005	—	—	—	—
1 P.L.C.	± .005	—	—	—	—
2 P.L.C.	± 0.005 (.002)	—	—	—	—
3 P.L.C.	± .005	—	—	—	—
4 P.L.C.	± .005	—	—	—	—
ANGLES	± .005	—	—	—	—
MATERIAL	FINISH	WEIGHT	SCALE	DRAWING NO	RESTRICTED TO
△	△	—	1:1	A0 00779 1738019	—
CUSTOMER DRAWING		SCALE		SHEET	REV
				1 of 1	0