

a vital part of your world

Text Search:

Saturday, 7 January, 2006

CATALOG

 • **Cross Reference**

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

 e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Switches, Shunts, and Knobs
↳ Slide Switches

 Alcoswitch **TSS21NGRA** [Active](#)

Not ELV or RoHS Compliant

(Corporate P/N: 2-1437579-0)
[Search for Compliant \(RoHS/ELV\) Alternates](#)
[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ✦ General Info ✦ Sales Info 	<ul style="list-style-type: none"> ✦ Pricing & Availability 	<ul style="list-style-type: none"> ✦ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)
Searchable Features:

Brand:	Alcoswitch
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Wave solder capable to 240°C, Wave solder capable to 265°C
Number of Positions:	2
Configuration (Pole-Throw):	Double Pole - Double Throw
Actuator Style:	Side
Actuator Color:	Black
Series:	TSS
Mount Style:	Through-Hole
Mount Angle:	Right Angle
Terminal Configuration:	Standard
Operating Function:	On None On
Contact Plating:	Gold
Contact Rating:	0.4 VA max @ 20 VDC or peak AC
PCB Tail Length (mm [in]):	3.30 [0.130]
Termination Type:	PC

Other Properties:

Contact Material:	Copper
Stamped Marking:	Yes
Number of Actuators:	Single
Actuator Material:	Polyester
Flammability Rating:	UL 94V-0

[Copyright and Privacy Statement](#)
 Visit [Tyco International Ltd.](#)

