



a vital part of your world

Find Answers:

Saturday, 15 October, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

AMPMODU

↳ .100 Inch Centerline-AMPMODU Headers

AMP 103322-2 Active

Not ELV or RoHS Compliant

(Corporate P/N: 103322-2)

Search for Compliant (RoHS/ELV)

Alternates

CAD Geometry | Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ▾ General Info ▾ Sales Info ▾ Assembly Subcontractors 	<ul style="list-style-type: none"> ▾ Pricing ▾ Product Availability 	<ul style="list-style-type: none"> ▾ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Wave solder capable to 240°C
Product Type:	Header
Header Type:	Breakaway
Number of Rows:	Dual
Number of Positions:	4
Mating Post Length (mm [in]):	8.08 [0.318]
Centerline, Matrix (mm [in]):	2.54 x 2.54 [.100 x .100]
Mount Angle:	Vertical
Selectively Loaded:	No

Other Properties:

Post Size (mm [in]):	0.64 [.025]
Contact Shape:	Square
Contact Material:	Phosphor Bronze
Contact Termination Area Plating:	Tin-Lead over Nickel
Housing Flammability Rating:	UL 94V-0
Operating Temperature (°C):	-65 – +105
Current Rating (Amps.):	3
Insulation Resistance (M•):	5,000
Dielectric Withstanding Voltage (V):	750

PCB Retention Feature:	Without
Housing Material:	Thermoplastic
Surface Mount Compatible:	No
Contact Mating Area Plating:	Tin-Lead
Board Standoff:	Without
Mounting Ears:	Without
Panel Attachment:	No
Mating Connector Lock:	Without
High Temperature Housing:	No
High Speed Serial Data Connector:	No
Termination Post Length (mm [in]):	3.18 [0.125]
Mount Type:	PC Board

Approved Standards:	UL E28476, CSA LR7189
Comment:	Headers may be broken to desired number of positions using Hand Tool No. 91406-1, or Tool Kit No. 314818-1. Other tail lengths are available, consult Tyco Electronics.

[Copyright and Privacy Statement](#)
 Visit [Tyco International Ltd.](#)

[\[Products | Catalog | Brands | Industries | Commerce | Supplier | Contact Us | About | Home \]](#)