



Email

Products Industries

Resources

About TE

My Account

Innovation


Support Center

■ Share

What can we help you find?

Home > Products > RF & Coax > Product Feature Selector > Product Details

1-1337402-0 Product Details



N Series RF Connectors

N Str Plg MC 500hm Silver Pltd PSF 1/4M,

1-1337402-0 🥖

TE Internal Number: 1-1337402-0

Product Highlights View All

- · Connector RF
- Plug
- Coaxial Cable Termination Type = MIL-Clamp
- Applies To Cable
- Coaxial Cable Type (RG/U or Mfg.) = PSF 1/4M, 8A, URM 67, 213, Raychem 5012A1422, Raychem 5012E1339, Raychem 5012E1632, Raychem EPD 29108Q, Raychem EPD 71535Q

Pricing & Availability	>
Request Sample	>
Add to My Part List	+
Buy Product through Distributor	>

Related Products

you're looking for?

Find Similar Products

View Part in Product Feature Selector

Check for Tooling

Not quite the product

Print

Documents

Features

Compliance

Please Note: Use the Product Drawing for all design activity

Product Type Features	•	
Product Type ?	Connector - RF	
Gender ?	Plug	
Wire/Cable Type	Coaxial Cable	
Grade ?	Commercial	
Lightning/EMP Protection	None	
Dielectric Material ?	PTFE	
Weatherproof	No	
Flats Dimension	15.8 A/F	
Coupling Nut Material	Brass	
Mechanical Attachment		
Panel Mount Retention	Without	
Electrical Characteristics		
Frequency	DC - 11 GHz	
Connector Impedance (Ω)	50	
Termination Features		

Dielectric Material 🔞	PTFE	
Weatherproof	No	
Flats Dimension	15.8 A/F	
Coupling Nut Material	Brass	
Mechanical Attachment	İ.	
Panel Mount Retention	Without	
Electrical Characteristics		
Frequency	DC - 11 GHz	
Connector Impedance (Ω)	50	
Termination Features		
Coaxial Cable Termination Type	MIL-Clamp	
Body Features		
Body Style ?	Straight	
Body Plating ?	Silver	
Body Material	Brass	

White Silicone Rubber

Contact Features	
Captured Center Contact	With
Center Contact Plating	Silver
Center Contact Material	Brass
Configuration Features	
	PSF 1/4M, 8A, URM 67, 213, Raychem

Coaxial Cable Type (RG/U or Mfg.) ?	213, Raychem 5012A1422, Raychem 5012E1339, Raychem 5012E1632, Raychem EPD 29108Q, Raychem EPD 71535Q
Industry Standards	
Covernment/Industry	

-	
Government/Industry Qualification	No
RoHS/ELV Compliance	RoHS compliant, ELV compliant
Lead Free Solder Processes ?	Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
RoHS/ELV Compliance History	Converted to comply with RoHS directive
Military Style Number	UG-21D/U
Environmental Operating Temperature (Max.) (°C)	165
Conditions for Usage	
Applies To	Cable
Packaging Features	
Packaging Method	Individual
Packaging Quantity	50

Corporate Information

Gasket Material

About TE Investors News Room Supplier Portal Careers

Terms & Conditions Privacy Policy Global Accessibility Statement Quick Links

Site Map

Distributor Inventory Product Cross Reference Documents & Drawings Product Compliance Support Center

Other

Brand

Customer Support Email or Chat With Us

Greenpar

Find a Phone Number Knowledge Base Manage Your Account Keep Me Informed







