

Mini-SAS

1. PURPOSE 目的

Define the packaging specification and packaging method of Mini-SAS.

订定 Mini-SAS 产品之包装规格及包装方式。

2. APPLICABLE PRODUCT 适用范围

Product Part NO.	Description
2127833-X	CABLE ASSEMBLY,MINI-SAS, 4X, EXTERNAL 6 Gbps, PASSIVE

3. PACKAGING MATERIAL 包装材料

Product Part No.	Inner pkg					Outer pkg										
	Bubble Bag	PE Bag			Inner Label	Bubble Pack		Box				Outer Label	UL Label			Pkg qty
	623880-3	1533282-3	1533282-4	1533282-5	623865-4	110455-2	623881-5	12120-1	115216	12140-1	1533040-4	623865-5	623227-6	623227-7	623227-8	pcs/box
2127833-1	2/1	1/1	-	-	1/1	4/50	-	-	1/50	-	-	1/50	-	-	2/50	50
2127833-2	2/1	1/1	-	-	1/1	4/25	-	-	1/25	-	-	1/25	-	-	1/25	25
2127833-3	2/1	1/1	-	-	1/1	4/25	-	-	1/25	-	-	1/25	-	-	1/25	25
2127833-4	2/1	1/1	-	-	1/1	4/25	-	-	1/25	-	-	1/25	-	-	1/25	25
2127833-5	2/1	-	1/1	-	1/1	4/25	-	-	1/25	-	-	1/25	-	-	1/25	25
2127833-6	2/1	-	1/1	-	1/1	4/25	-	-	1/25	-	-	1/25	-	-	1/25	25
2127833-7	2/1	-	1/1	-	1/1	4/20	-	-	1/20	-	-	1/20	-	2/20	-	20
2127833-8	2/1	-	1/1	-	1/1	4/20	-	-	1/20	-	-	1/20	-	2/20	-	20
2127833-9	2/1	-	1/1	-	1/1	4/10	-	-	1/10	-	-	1/10	-	1/10	-	10
1-2127833-0	2/1	-	-	1/1	1/1	4/5	-	-	4/5	-	-	1/5	1/5	-	-	5
1-2127833-1	2/1	-	-	1/1	1/1	4/5	-	-	4/5	-	-	1/5	1/5	-	-	5
1-2127833-2	2/1	-	-	1/1	1/1	4/5	-	-	4/5	-	-	1/5	1/5	-	-	5
1-2127833-3	2/1	-	-	1/1	1/1	4/5	-	-	4/5	-	-	1/5	1/5	-	-	5
1-2127833-4	2/1	1/1	-	-	1/1	4/50	-	-	1/50	-	-	1/50	-	-	2/50	50
1-2127833-5	2/1	1/1	-	-	1/1	2/25	-	1/25	-	-	-	1/25	-	-	1/25	25
1-2127833-6	2/1	1/1	-	-	1/1	4/25	-	-	1/25	-	-	1/25	-	-	1/25	25

DR Sam Wu	CHK Link Tian	APVD Ansin Yang
--------------	------------------	--------------------

3. PACKAGING MATERIAL 包装材料

Product Part No.	Inner pkg					Outer pkg										Pkg qty pcs/box
	Bubble Bag	PE Bag			Inner Label	Bubble Pack	Box				Outer Label	UL Label				
	623880-3	1533282-3	1533282-4	1533282-5	623865-4	110455-2	623881-5	12120-1	115216	12140-1	1533040-4	623865-5	623227-6	623227-7	623227-8	
1-2127833-7	2/1	1/1	-	-	1/1	4/25	-	-	1/25	-	-	1/25	-	-	1/25	25
1-2127833-8	2/1	-	1/1	-	1/1	4/25	-	-	-	1/25	-	1/25	-	-	1/25	25
1-2127833-9	2/1	-	1/1	-	1/1	2/25	-	-	-	1/25	-	1/25	-	-	1/25	25
2-2127833-0	2/1	-	1/1	-	1/1	2/10	-	-	1/10	-	-	1/10	-	1/10	-	10
2-2127833-1	2/1	-	-	1/1	1/1	-	2/10	-	-	-	1/10	1/10	-	1/10	-	10
2-2127833-2	2/1	-	-	1/1	1/1	-	2/10	-	-	-	1/10	1/10	-	1/10	-	10
2-2127833-3	2/1	-	1/1	-	1/1	6/5	-	-	1/5	-	-	1/5	1/5	-	-	5
2-2127833-4	2/1	-	-	1/1	1/1	-	8/5	-	-	-	1/5	1/5	1/5	-	-	5
2-2127833-5	2/1	-	-	1/1	1/1	-	6/5	-	-	-	1/5	1/5	1/5	-	-	5
2-2127833-6	2/1	-	-	1/1	1/1	-	6/5	-	-	-	1/5	1/5	1/5	-	-	5

	Inner	Middle	Outer
LABEL	623865-4	-	623865-5
SEALING	Tape	-	Tape

4. PACKING METHOD 包装方法

4.1. Place the connector into bubble bag and tie it with wire.

将产品的连接头放入气泡袋并用扎带包扎好。

4.2. Coil cable to fit box & into relevant polybag and seal with two small tape.

盘绕适当大小尺寸(依据袋子及箱子)的CABLE后放入相应的塑料袋中并用两小块透明胶布封好其开口。

4.3. Place an inner label in the middle of the bag.

在袋子中央贴一内标签。

4.4. Set up a box and secure bottom flaps with tape.

折叠好一包装箱，并用胶带封好箱底。

4.5. Place proper bubble pack based on 3. into the bottom of box, bubble facing down.

根据3中的用量在箱底放入适当的气泡垫，气泡面朝下。

注：上下气泡垫的用量一样。

4. PACKING METHOD 包装方法

4.6. Place proper qty bags of cabel (as step 4 shows) into box.

按4中规定数量将产品整齐放入箱中, 产品之间连接头错开放置.

注: 其中2-2127833-3/4/5/6, 每袋产品之间需用一块气泡垫隔开。

4.7. Place proper bubble pack based on 3. on the top of cables, bubble facing up.

根据3中的用量在CABLE的上面放入适当的气泡垫, 气泡面朝上。

注: 上下的气泡垫的用量一样。

4.8. Seal the box with tape. And place product identification label & UL label in "product id" marked on box.

用胶带封箱, 在箱外印有“PRODUCT ID”标识处贴上外标签和UL标签。