


Product Details for 1 -390262 -7



1 -390262 -7

[Active](#)

DIP Sockets

[RoHS Compliant \(Statement of Compliance\)](#)

Product Highlights:

- ? [DIP Socket](#)
- ? [Number of Positions = 48](#)
- ? [Row-to -Row Spacing = 15.24 mm](#)
- ? [Thru Hole](#)
- ? [Mount Style = Vertical](#)

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [DIP SOCKET, .600 CENTER LINE LADDER STYLE](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? [None Available](#)

Product Specifications:

- ? [None Available](#)

Application Specifications:

- ? [None Available](#)

Instruction Sheets:

- ? [None Available](#)

CAD Files:

- ? [None Available](#)

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Product Type](#) = DIP Socket
- ? [Number of Positions](#) = 48
- ? [Profile](#) = Standard
- ? [Frame Style](#) = Ladder
- ? [Leg Style](#) = Straight
- ? [PCB Mount Angle](#) = Horizontal

Electrical Characteristics:

- ? [Insulation Resistance \(M?\)](#) = 10,000
- ? [Contact Resistance \(m?\)](#) = 30

Termination Related Features:

- ? [Termination Post Length \(mm \[in\]\)](#) = 3.00 [0.118]

Body Related Features:

- ? [Row-to -Row Spacing \(mm \[in\]\)](#) = 15.24 [0.600]
- ? [Mount Style](#) = Vertical
- ? [Centerline \(mm \[in\]\)](#) = 2.54 [0.100]

Contact Related Features:

- ? [Contact Mount](#) = Thru Hole
- ? [Contact Material](#) = Phosphor Bronze
- ? [Contact Mating Area Plating](#) = Tin
- ? [Contact Style](#) = Stamped + Formed
- ? [Mating Contact Type](#) = Dual Leaf

Configuration Related Features:

- ? [Height Above PC Board \(mm \[in\]\)](#) = 5.10 [0.200]

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? [RoHS/ELV Compliance History](#) = Always was RoHS compliant

Conditions for Usage:

- ? [Temperature Range \(°C\)](#) = -40 - +105

Packaging Related Features:

- ? [Packaging Method](#) = Tube

Other:

- ? [Brand](#) = AMP