




CONNECTORS

BARRIER STRIPS



✓ Active

↓ **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE)

6PCV-06-716=6PCV SPECIAL

Buchanan

1437653-1

TE Internal Number: 1437653-1

Alias ID: 6PCV-06-716

Always EU RoHS/ELV Compliant

Barrier Style **Tri-Barrier**

Bottom Termination Style **Printed Circuit Pin**

Current Rating (A) **5, 25**

Centerline **9.53 mm [.375 in]**

Number of Positions **6**



Product Drawings

[6PCV-XX-007 ASSEMBLY](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Block Style

Open Bottom with Standoffs

Product Type

Barrier Strip

Applies To

Printed Circuit Board

Configuration Features

Number of Positions

6

Number of Rows

1

Number of Levels

1

Electrical Characteristics	Current Rating (A)	5, 25
	Voltage (V)	300, 600
	Current Rating (Max) (A)	25
Body Features	Barrier Style	Tri-Barrier
	Color	Black
Contact Features	Terminal Material	Copper Alloy
	Terminal Plating Finish	Bright
	Terminal Plating Material	Tin
Termination Features	Bottom Termination Style	Printed Circuit Pin
Mechanical Attachment	Mounting Options	None
	Screw Material	Steel
	Screw Plating Material	Zinc Chromate
	Mounting Insert	Without
	Mounting Angle	Vertical
	Mounting Style	Direct (All Positions Filled)
	Mounting Ears	Without
	Screw Size	6-32
	Screw Head Type	Combo Phil-Slot
Housing Features	Centerline	9.53 mm [.375 in]
	Housing Material	Thermoplastic
Dimensions	Wire Range	22 – 12 AWG [.326 – 3.31 mm²]
	Length	58.7 mm [2.311 in]
Usage Conditions	Operating Temperature Range	105 °C [221 °F]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	115
	Packaging Method	Package

[VIEW ALL PRODUCT COMPLIANCE](#)

