


**Product Details for 033 - 0036 - 0001**



**033 - 0036 - 0001**

Tyco Part Number: 1467943 - 1

[Active](#)

**SMB RF Connectors**

[RoHS Compliant \(Statement of Compliance\)](#)

**Product Highlights:**

- ? Adapter
- ? Jack
- ? Miniature
- ? Adapter Type = SMB Jack - Jack Feed - Thru
- ? Coupler Style = Threaded

[View all Features](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- ? [ADAPTER, S-93](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- ? None Available

**Product Specifications:**

- ? None Available

**Application Specifications:**

- ? None Available

**Instruction Sheets:**

- ? None Available

**CAD Files:**

- ? None Available

**Additional Information:**

- ? [Product Line Information](#)

**Related Products:**

- ? [Tooling](#)

[List all Documents](#)

**Product Features** (Please use the Product Drawing for all design activity)

**Product Type Features:**

- ? [Product Type](#) = Adapter
- ? [Gender](#) = Jack
- ? Connector Series = Miniature
- ? [Adapter Type](#) = SMB Jack - Jack Feed - Thru
- ? [Body Style](#) = Straight
- ? [Grade](#) = Commercial
- ? Safety Wire Holes = Without
- ? Body Material = Brass
- ? Dielectric Material = TEFLON

**Mechanical Attachment:**

- ? [Panel Attachment](#) = Without

**Electrical Characteristics:**

- ? [Connector Impedance \(?\)](#) = 93
- ? Environmental Seal = Without
- ? Hex Head Size (Across Flats) (mm [in]) = 7.92 [0.312]

**Body Related Features:**

- ? Coupler Style = Threaded
- ? [Pin Protection](#) = Without
- ? [Body Plating](#) = Silver
- ? Overall Length (mm [in]) = 10.41 [0.410]
- ? Mates With = 93 Ohm Screw - On (S - 93)

**Contact Related Features:**

- ? [Center Contact Plating](#) = Gold per MIL - G-45204, Type II, Grade C, Class 1
- ? Contacts = With

**Industry Standards:**

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in -Paste capable to 245°C, Pin in -Paste capable to 260°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

**Other:**

- ? Brand = Microdot