Email

Share

Quick Links

Print

Check Pricing & Availability

Contact Us About This Product

Search for Tooling

▶ View Connectors (2) Product Feature Selector

1-533268-2 Product Details



5 of 6 EU RoHS/ELV Compliant (Find RoHS Compliant

Alternates/Statement of Compliance)

- Product Highlights: Connector
- Receptacle
- 225 Positions
- PCB Mount Style = Through Hole

. PCB Mounting Orientation = Right Angle


View all Features

TE Internal Number: 1-533268-2 Active

View 3D PDF

1-533268-2







Documentation & Additional Information

Product Drawings:

HDI, 3 ROW, RECEPTACLE ASSEMBLY, 3.05 [.120] LONG SO... (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

· Connector, Interconnect, High Density (PDF, English)

Application Specifications:

· AMP-HDI Connectors (PDF, English)

Instruction Sheets:

AMP-HDI* High Density Interconnection Printed Circui... (PDF, English)

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version M)
- 3D Model (IGES, Version M)
- . 3D Model (STEP, Version M)

Additional Information:

Product Line Information

Related Products:

- Tooling
- Connectors (2)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

Termination Features:

- Product Type = Connector
- Gender = Receptacle
- PCB Mount Style = Through Hole
- PCB Mounting Orientation = Right Angle
- Make First / Break Last = No
- PCB Mount Retention = Without

· Solder Tail Contact Plating = Tin

Housing Features:

List all Documents

- . Mating Alignment = Without
- Housing Material = PPS
- Housing Color = Brown
- · Housing Material Temperature = High

Configuration Features:

• Center Guide = Without

Industry Standards:

- Government/Industry Qualification = No
- RoHS/ELV Compliance = ELV compliant, 5 of 6 Compliant
- Lead Free Solder Processes = Not suitable for lead free processing

Other:

Brand = AMP

Body Features:

- Number of Positions = 225
- Number of Rows = 3
- Centerline (mm [in]) = 2.54 [0.100]

Contact Features:

- Contact Configuration = Four-Beam
- Contact Plating, Mating Area, Material = Gold (30)

Termination Post Length (mm [in]) = 3.05 [0.120]

- Contact Base Material = Copper Alloy
- Underplate Material = Nickel

Corporate Information

About TE

Investors

News Room

Supplier Portal

Check Distributor Inventory Cross Reference Products Find Documents & Drawings

Careers Site Map

Quick Links

Product Compliance Support Center

Customer Support Email or Chat With Us Find a Phone Number Search Knowledge Base Manage Your Account

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address











