


201297-1 Product Details

Share Print Email



201297-1

TE Internal Number: 201297-1
 Active

View 3D PDF

M Series Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Product Series = M Series
- Connector
- Cable-to-Cable / Cable-to-Panel
- Applies To Panel, Applies To Wire/Cable
- Housing

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Add to My Part List Request Sample Find Similar Products Buy Product

Documentation & Additional Information

Product Drawings:

- [BLOCK, MALE, 14 PLACE, MINIATURE RECTANGULAR, M SERIES \(PDF, English\)](#)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- [AMP 14 Position Series "M" -SM & "M" -DM Connectors \(PDF, English\)](#)
- [AMP* 6, 14, 20 AND 41 POSITION SERIES "M" CONNECTORS \(PDF, English\)](#)

CAD Files: (CAD Format & Compression Information)

- [2D Drawing \(DXF, Version S\)](#)
- [3D Model \(IGES, Version S\)](#)
- [3D Model \(STEP, Version S\)](#)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Series = M Series
- Product Type = Connector
- Connector Type = Housing
- Strain Relief = Without
- Sealed = No

Mechanical Attachment:

- Panel Mount Retention = With
- Panel Mount Retention Type = Screw Mount

Dimensions:

- Length (X-Axis) (mm [in]) = 19.23 [0.757]
- Width (Z-Axis) (mm [in]) = 11.18 [0.440]
- Profile Height (Y-Axis) (mm [in]) = 31.75 [1.250]

Body Features:

- Mating Retention = Without

Contact Features:

- Contact Type = Pin

Housing Features:

- Connector Style = Plug
- Centerline (mm [in]) = 3.30 [0.1299]
- Housing Material = Phenolic - GF
- Housing Color = Black
- Mating Alignment = Without
- UL Flammability Rating = UL 94V-0

Configuration Features:

- Number of Positions = 14

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- [RoHS/ELV Compliance History](#) = Always was RoHS compliant

Environmental:

- Operating Temperature (°C [°F]) = -55 - +150 [-67 - +302]

Conditions for Usage:

- Applies To = Panel, Wire/Cable
- For Use With = Repectacle Block 201298

Operation/Application:

- Application Use = Cable-to-Cable / Cable-to-Panel

Packaging Features:

- Packaging Method = Carton
- Packaging Quantity = 261

Other:

- Brand = AMP
- Comment = Housing accepts Type II, #20 contacts.

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

