



a vital part of your world

Find Answers:

Wednesday, 16 November, 2005

CATALOG

- ➔ Cross Reference
  - [Competitive Products](#)
  - [Military Spec P/Ns](#)
  - [Tyco Brand P/Ns](#)

- ➔ [Part Number Search](#)
- ➔ [Document Search](#)
- ➔ [Product Type Search](#)
- ➔ [Product Family Search](#)
- ➔ [Alphabetical Search](#)
- ➔ [RoHS/ELV Compliance & Alternates](#)
- ➔ [CAD Model Search](#)
- ➔ [Brand Search](#)
- ➔ [Tool Search](#)
- ➔ [Multiple Part Comparison](#)
- ➔ [Lead Free Solutions](#)
- ➔ [Help/Glossary](#)

[Home](#)

e-bulletin newsletter  
**SUBSCRIBE NOW!**  
 click here

## Multimate Contacts

➔ **Multimate**

**AMP** 201334-1 [Active](#)

**Directive 2002/95/EC Compliant**

[RoHS Compliant](#)

**(Corporate P/N: 201334-1)**

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> <li>➤ <a href="#">General Info</a></li> <li>➤ <a href="#">Sales Info</a></li> <li>➤ <a href="#">Assembly Subcontractors</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Pricing &amp; Availability</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Tooling</a></li> </ul>

Searchable Features:	
<b>Brand:</b>	AMP
<b><a href="#">RoHS/ELV Compliance:</a></b>	RoHS compliant, ELV compliant
<b><a href="#">Lead Free Solder Processes:</a></b>	Not relevant for lead free process
<b><a href="#">Pin/Socket:</a></b>	Pin
<b>High Current:</b>	No
<b><a href="#">Contact Mating Area Plating:</a></b>	Gold (30) over Nickel (50)
<b><a href="#">Wire Range (mm [AWG]):</a></b>	0.08-0.20 <sup>2</sup> [28-24]
<b><a href="#">Insulation Diameter (mm [in]):</a></b>	1.22 – 1.65 [0.048 – 0.065]
<b><a href="#">Contact Material:</a></b>	Brass
<b>Product Type:</b>	Type II

Other Properties:	
<b>Pin Diameter (mm [in]):</b>	1.57 [0.062]
<b>Wire/Cable Type:</b>	Discrete Wire
<b>Test Current (Amps.):</b>	13.0
<b>Color Code:</b>	Red/Red
<b>Grade:</b>	Commercial
<b>Used With:</b>	G Series Connectors, M Series Connectors, CPC Connectors
<b>Contact Retention Method:</b>	Retention Spring
<b>Retention Spring Material:</b>	Stainless Steel

<b>Contact Size:</b>	16
<b>Contact Type:</b>	Signal
<b>Terminate To:</b>	Wire
<b>Insulation Support:</b>	Yes
<b>Wire Termination Type:</b>	Crimp
<b>Packaging Method:</b>	Loose Piece

**Comment:** Use turret TH502 (p/n 1-601967-6) with hand tool 601967-1. Extraction Tool No. 305183  
Insertion Tool No. 200893-2 (for insulation diameters 1.78 [.070] or less).

[Copyright](#) and [Privacy Statement](#)  
Visit [Tyco International Ltd.](#)

[ [Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#) ]