

**CATALOG**

**Cross Reference**

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)


- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter  


**Multimate Contacts**

↳ **Multimate**

**AMP** 202237-2  [Active](#)

[Not ELV or RoHS Compliant](#)

**(Corporate P/N: 202237-2)**

[Search for Compliant \(RoHS/ELV\)](#)

[Alternates](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

**Related Part Information**

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> <li>↳ <a href="#">General Info</a></li> <li>↳ <a href="#">Sales Info</a></li> <li>↳ <a href="#">Assembly Subcontractors</a></li> </ul>	<ul style="list-style-type: none"> <li>↳ <a href="#">Pricing &amp; Availability</a></li> </ul>	<ul style="list-style-type: none"> <li>↳ <a href="#">Tooling</a></li> </ul>

**Photos & Line Drawings** - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

**Searchable Features:**

<b>Brand:</b>	AMP
<b><a href="#">RoHS/ELV Compliance:</a></b>	Not ELV/RoHS compliant
<b><a href="#">Lead Free Solder Processes:</a></b>	Not relevant for lead free process
<b><a href="#">Pin/Socket:</a></b>	Socket with Solder Tab
<b>High Current:</b>	No
<b><a href="#">Contact Mating Area Plating:</a></b>	Bright Tin-Lead
<b><a href="#">Contact Material:</a></b>	Brass
<b><a href="#">Termination End Plating:</a></b>	Bright Tin-Lead
<b>Product Type:</b>	Type III+
<b><a href="#">Contact Size:</a></b>	16

**Other Properties:**

<b>Pin Diameter (mm [in]):</b>	1.57 [0.062]
<b>Wire/Cable Type:</b>	Discrete Wire
<b>Test Current (Amps.):</b>	13.0
<b>Spring Material:</b>	Stainless Steel
<b>Grade:</b>	Commercial
<b>Solder Tab Plating:</b>	Bright Tin-Lead
<b>Used With:</b>	M Series Connectors, CPC Connectors
<b>Comment:</b>	These contacts can be used in Multimate contact cavities of all connector housings.

<b><u>Contact Type:</u></b>	Signal
<b><u>Terminate To:</u></b>	Wire
<b><u>Post Type:</u></b>	Solder Tab
<b><u>Insulation Support:</u></b>	No
<b><u>Wire Termination Type:</u></b>	Solder
<b><u>Packaging Method:</u></b>	Loose Piece

[Copyright](#) and [Privacy Statement](#)  
Visit [Tyco International Ltd.](#)

[ [Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#) ]

.