

a vital part of your world

Text Search:

Friday, 25 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

 e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Subminiature and Microminiature D Connectors
↳ Hardware (AMPLIMITE)
AMP 206514-1 [Active](#)
[Not ELV or RoHS Compliant](#)
(Corporate P/N: 206514-1)
[Search for Compliant \(RoHS/ELV\) Alternates](#)
[CAD Geometry](#) | [Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ✦ General Info ✦ Sales Info ✦ Assembly Subcontractors 	<ul style="list-style-type: none"> ✦ Pricing & Availability 	<ul style="list-style-type: none"> ✦ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:	
Brand:	AMP
Government/Industry Qualification:	No
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Not relevant for lead free process
Product Type:	Locking Post Assembly
Thread Size:	4-40 UNC
Packaging Method:	Individual Kit

Other Properties:	
Locking Post Material:	Steel
Locking Post Plating:	Zinc
Locking Post Finish:	Yellow Chromate
Comment:	Locking posts with 2-56 thread size are to be used with cable clamps with mounting flanges. Locking posts with 4-40 thread size can be used with all other cable clamps. All parts are packaged unassembled. For front panel mounting, it is recommended that a shim be used between the connector flange and panel to prevent bowing of the flange. Each kit is comprised of two complete assemblies. Locking posts mate with slide latches.

[Copyright and Privacy Statement](#)
 Visit [Tyco International Ltd.](#)