a vital part of your world

Tuesday, 22 November, 2005

## **CATALOG**

Cross Reference

**Competitive Products** Military Spec P/Ns Tyco Brand P/Ns

- Part Number Search
- Document Search
- Product Type Search
- Product Family Search
- Alphabetical Search
- → RoHS/ELV Compliance & Alternates
- CAD Model Search
- Brand Search
- \* Tool Search
- → Multiple Part Comparison
- → Lead Free Solutions
- → Help/Glossary

## **Home**

e-bulletin newsletter SUBSCRIBE NOW! click here

## **Soft Shell Connectors**

(Corporate P/N: 207441-3)

→ 5mm (.197") Centerline, 600 V, 14 A max. (Metrimate)

207441-3

Active

Not ELV or RoHS Compliant

Search for Compliant (RoHS/ELV) Alternates

**Search for Parts** 

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information			
General Information	eCommerce	Related Part Information	
<ul> <li>General Info</li> <li>Sales Info</li> <li>Assembly Subcontractors</li> </ul>	▶ Pricing & Availability	<b>→</b> Tooling	

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product or viewing purposes only.

## **Product Photo**

Searchable Features:		
Brand:	AMP	
RoHS/ELV Compliance:	Not ELV/RoHS compliant	
Lead Free Solder Processes:	Wave solder capable to 240° C, Wave solder capable to 265° C	
Product Type:	Header	
Connector Configuration:	Square Grid	
Number of Positions:	9	
Gender:	Pin	
Coaxial Socket:	Without	
Keyed:	No	
Mount:	Printed Circuit Board	
PCB Mount Angle:	Vertical	

Other Properties:		
Mating Connector Lock Type:	Locking Tab	
Contact Mating Area Plating:	Gold (30)	
Contact Termination Area Plating:	Tin Lead over Nickel	
Contact Material:	Copper Alloy	
PCB Retention Method Feature:	Mounting Holes	
Voltage (VAC):	600	
Current Rating (Amps.):	14	
Housing Material:	Thermoplastic	
Housing Color:	Red	
Housing Flammability Rating:	UL 94V-0	
Comment:	Pin and socket headers do not mate.	

<b>Mounting Ears:</b>	With
Centerline (mm [in]):	5.00 [0.197]
Post Type:	Solder Post
Termination Post Length (mm [in]):	4.60 [0.181]
Mating Connector Lock:	With
Jackscrew:	Without
<u>8/32 Insert:</u>	No
PCB Retention Feature:	Yes

Copyright and Privacy Statement
Visit Tyco International Ltd.

[ Products | Catalog | Brands | Industries | Commerce | Supplier | Contact Us | About | Home ]