

a vital part of your world

Find Answers:

Monday, 31 October, 2005

CATALOG

. Cross Reference

Competitive Products Military Spec P/Ns Tyco Brand P/Ns

- Part Number Search
- Document Search
- * Product Type Search
- Product Family Search
- * Alphabetical Search
- * RoHS/ELV Compliance & Alternates
- * CAD Model Search
- Brand Search
- * Tool Search
- Multiple Part Comparison
- Lead Free Solutions
- Help/Glossary

Home

e-bulletin newsletter SUBSCRIBE NOW! click here

Subminiature and Microminiature D Connectors → Hardware (AMPLIMITE)

AMP

207952-1



Active

(Corporate P/N: 207952-1)

Not ELV or RoHS Compliant

Search for Compliant (RoHS/ELV)

Alternates Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is

Related Part Information		
General Information	eCommerce	Related Part Information
 General Info Sales Info Assembly Subcontractors 	Pricing & Availability	: Tooling

currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5

and Netscape 6, as well as all later versions of these browsers.

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

Product Photo

Searchable Features:		
Brand:	AMP	
Government/Industry Qualification:	No	
RoHS/ELV Compliance:	Not ELV/RoHS compliant	
<u>Lead Free Solder</u> <u>Processes:</u>	Not relevant for lead free process	
Product Type:	Female Screw Locks	
Thread Size:	4-40 UNC	
Thread Length (mm [in]):	6.35 [0.250]	
Screwlock Style:	Screwlock with Flat Washers and Square Nuts	
Screw Finish:	Yellow Chromate	

Other Properties:			
Screw Plating:	Zinc		
Screw Material:	Steel		
For Use With:	All Plastic Right-Angle Connectors (HD)		
Comment:	All parts are packaged unassembled. Each female screwlock kit is comprised of two assemblies. Female screwlocks mate with male screw retainers. Short female screwlocks cannot be used with HDF connectors. One or two flat washers (4 included) may be required for panel thicknesses less than 1.52 [.060]. Female screwlocks are not recommended for panel thicknesses greater than 1.52 [.060].		

Packaging Method:

Individual Kit

<u>Copyright</u> and <u>Privacy Statement</u> Visit <u>Tyco International Ltd.</u>

[Products | Catalog | Brands | Industries | Commerce | Supplier | Contact Us | About | Home]

ı