

213788 -2 Product Details

No Image Available

213788 -2

 [Active](#)

5mm (.197") Centerline, 600 V, 14 A max. (Metrimate)

[Not ELV or RoHS Compliant](#) (Find RoHS Compliant Alternates)

Product Highlights:

- ? Header
- ? Rectangular Connector Configuration
- ? Number of Positions = 62
- ? Receptacle
- ? Without Coaxial Socket

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [HEADER ASSEMBLY, 62 POSN, ACTION PIN TM](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? [APPLICATION SPECIFICATION, METRIMATE DRAWER CONNECTORS](#) (PDF, English)
- ? [Metrimate Self -Locking Connectors](#) (PDF, English)
- ? [METRIMATE Self -Locking Connectors](#) (PDF, English)

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Product Type](#) = Header
- ? [Number of Positions](#) = 62
- ? [Gender](#) = Receptacle
- ? [Keyed](#) = No
- ? [Mount](#) = Panel Mount
- ? [Mounting Ears](#) = Without
- ? [Post Type](#) = Compliant Post
- ? [Mating Connector Lock](#) = Without
- ? PCB Retention Feature = No

Termination Related Features:

- ? Termination Post Length (mm [in]) = 5.59 [0.220]

Body Related Features:

- ? [Connector Configuration](#) = Rectangular
- ? Coaxial Socket = Without
- ? [Centerline \(mm \[in\]\)](#) = 5.00 [0.197]
- ? [Jackscrew](#) = Without
- ? [8/32 Insert](#) = No

Contact Related Features:

- ? Contact Mating Area Plating = Gold (30) over Nickel (50)
- ? Contact Material = Phosphor Bronze

Housing Related Features:

- ? Housing Material = Polyester
- ? Housing Color = Black
- ? Housing Flammability Rating = UL 94V -0

Industry Standards:

- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Other:

- ? Brand = AMP