

Have a Question? Chat with a Product Information Specialist


What can we help you find?

Email

Buy Product

My Account Innovation About TE Products Industries Resources **Support Center**

2-1586017-4 Product Details



2-1586017-4

TE Internal Number: 2-1586017-4





VAL-U-LOK Series Connector System



Product Highlights:

- Wire-to-Wire
- Applies To Wire/Cable
- Connector
- Glow Wire Rating = Standard Part Not Glow
- Housing

View all Features

Add to My Part List

Quick Links

Share

- Pricing & Availability
- Search for Tooling
- View Mating Products (2) Product Feature Selector
- Contact Us About This Product

Print

Documentation & Additional Information

Product Drawings:

FREE HANGING PLUG HOUSING, V0, VAL-U-LOK(TM) (PDF, English)

Catalog Pages/Data Sheets:

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG (PDF, English)

Product Specifications:

VAL-U-LOK Connectors (PDF, English)

Application Specifications:

None Available

Instruction Sheets:

CAD Files: (CAD Format & Compression Information) • 2D Drawing (DXF, Version B)

- 3D Model (IGES, Version B)
- 3D Model (STEP, Version B)

Related Products:

- Mating Products (2)

Find Similar Products

Product Features (Please use the Product Drawing for all design activity)

List all Documents

Product Type Features:

- Product Type = Connector
- Connector Type = Housing
- Sealed = No
- UL File Number = E28476
- CSA File Number = 208567

Mechanical Attachment:

Mating Retention Type = Latching

Electrical Characteristics:

- Contact Current Rating, Max. (A) = 9
- Operating Voltage Reference = AC
- Operating Voltage (VAC) = 600

Termination Features:

· Termination Method to Wire/Cable = Crimp

Dimensions:

- Length (X-Axis) (mm [in]) = 51.60 [2.031]
- Width (Z-Axis) (mm [in]) = 23.90 [0.940]
- Profile Height (Y-Axis) (mm [in]) = 9.60 [0.378]

Body Features:

- Mating Retention = With
- Selectively Loaded = No

Contact Features:

- Contact Type = Pin
- Contact Design = Formed Pin

Housing Features:

- Connector Style = Plug
- Centerline (mm [in]) = 4.20 [0.165]
- Mating Alignment = With
- Mating Alignment Type = Keyed
- Housing Color = Natural
- UL Flammability Rating = UL 94V-0

Configuration Features:

Request Sample

- Number of Positions = 24
- Number of Rows = 2

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free
- RoHS/ELV Compliance History = Always was RoHS compliant
- Agency/Standard = CSA, UL
- UL Rating = Recognized

Identification Marking:

Circuit Identification Feature = With

Environmental:

Operating Temperature (°C [°F]) = -40 - +105 [-40 - +221]

- Conditions for Usage:
 Applies To = Wire/Cable
 - Glow Wire Rating = Standard Part Not Glow Wire

Operation/Application:

- Application Use = Wire-to-Wire
- Contact Transmits (Typical Application) = Signal (Data)
- Pick and Place Cover = Without

Packaging Features:

Packaging Method = Bag

Other:

• Brand = AMP

