




HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

CT BOX HDR V SMT 2P O/TAPE NAT

AMP CT | AMP CT

292175-2

TE Internal Number: 292175-2

Always EU RoHS/ELV Compliant

Centerline **2 mm [.079 in]**

Number of Positions **2**

PCB Mounting Orientation **Vertical**

PCB Mounting Style **Surface Mount**

Number of Rows **1**

Product Drawings

ON TAPING (EMBOSS) SMT TYPE POST HDR ASS'Y(V) W/O BOSS &WITH TAIL TYPE

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Product Specifications

Product Specification

AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PITCH, M/T TYPE, LEAD FREE VERSION

TIF
Japanese

AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PITCH, M/T TYPE, LEAD FREE VERSION

PDF
Japanese

AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PTICH, M/T TYPE, LEAD FREE VERSION

PDF
English

Product Environmental Compliance

TE Material Declaration

MD_292175-2_0827201109

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Vertical
	Product Type	Connector
	Connector Type	Header
	Shape	Rectangular
	Connector System	Wire-to-Board
	Wire/Cable Type	Discrete Wire
	Strain Relief	Without
	Sealed	No
	Connector Style	Header
Applies To	Printed Circuit Board	

Configuration Features	Number of Positions	2
	Number of Rows	1
	Tail Orientation	Inline
	Backwall/Post Interruptions	With

Electrical Characteristics	Operating Voltage	125 VAC [125 VDC]
----------------------------	-------------------	----------------------------

Body Features	Header Type	Shrouded
---------------	-------------	-----------------

Contact Features	Contact Mating Area Plating Material	Tin
	Contact Mating Area Plating Thickness	1 – 2 μm [39.37 – 78.73 μin]
	Contact Termination Area Plating Thickness	1 – 2 μm [39.37 – 78.73 μin]
	Contact Shape	Round
	Contact Termination Area Plating Material	Tin
	Contact Type	Pin
	Contact Transmits (Typical)	Signal (Data)
	Contact Current Rating (A)	4
	Contact Layout	Inline
	Contact Design	Round Post
Contact Base Material	Brass	

Termination Features	Termination Method to PC Board	Surface Mount
----------------------	--------------------------------	----------------------

Mechanical Attachment	PCB Mounting Style	Surface Mount
	PCB Mount Alignment	Without
	Mating Retention	Without
	PCB Mount Retention	With
	PCB Mount Retention Type	Solder Pads
	Contact Retention	With
	Mating Alignment Type	Polarization
	Panel Mount Retention	With
Housing Features	Mating Alignment	With
	Centerline	2 mm [.079 in]
Housing Features	Housing Color	Natural
	Housing Material	6T PA(GF)
Dimensions	Mating Post Length	4.5 mm [.177 in]
	PCB Thickness (Recommended)	.8 mm [.031 – .063 in]
	Height	7.8 mm [.307 in]
	Wire/Cable Size (AWG)	28 – 22
	Width	5.8 mm [.228 in]
	Insulation Diameter	.93 mm [.0366 – .041 in]
	Length	5.8 mm [.228 in]
Usage Conditions	Operating Temperature Range	-40 – 221 °C [-40 – 105 °F]
Operation/Application	For Use With	Printed Circuit Board
	Internal/External	Internal
	Pick and Place Cover	Without
Industry Standards	UL Flammability Rating	UL 94V-0
	UL File Number	E28476
	Agency/Standard	CSA, UL
	CSA File Number	LR 7189-133
Packaging Features	Packaging Method	Tape, Box
	Packaging Quantity	3500

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)