


**BNC Connectors, 50 Ohm (Continued)**


**Tee Adapters**

**Style A**  
(Jack-Plug-Jack)




**Style B**  
With Insulated  
Cover  
(Jack-Plug-Jack)

Insulation Material  
Polyphenylene oxide



**Style C**  
(Jack-Jack-Jack)



Style	Body Material and Plating	Center Contact Material and Plating	Dielectric	Dimensions			Comparable UG/U Connector	Packaging No. Per Pkg.	Part No.
				D	E	F			
A	Brass, Nickel	BE CU, Gold (30) <sup>1</sup>	TEFLON	32.54 1.291	26.19 1.031	14.27 .562	274A	Bulk (100)	221543-2
		BE CU, Silver (200) <sup>2</sup>	TEFLON	32.54 1.291	26.19 1.031	14.27 .562	274B	Individual (1)	329518
	Zinc, Nickel	PH BR, Gold (15) <sup>3</sup>	Acetal	33.02 1.300	27.31 1.075	14.50 .571	—	Bulk (100)	413592-2
		PH BR, Silver (200) <sup>3</sup>	Acetal	33.02 1.300	27.31 1.075	14.50 .571	—	Bulk (100)	413592-4
		BE CU, Gold (30) <sup>1</sup>	Acetal	33.02 1.300	27.31 1.075	14.50 .571	—	Bulk (100)	413592-6
		BE CU, Silver (200) <sup>2</sup>	Acetal	33.02 1.300	27.31 1.075	14.50 .571	—	Bulk (100)	413592-8
		PH BR, Gold (15) <sup>3</sup>	Acetal	33.02 1.300	27.31 1.075	14.50 .571	—	Individual (1) <sup>4</sup>	413592-9
		PH BR, Silver (200) <sup>3</sup>	Acetal	33.02 1.300	27.31 1.075	14.50 .571	—	Individual (1) <sup>4</sup>	1-413592-0
		BE CU, Silver (200) <sup>2</sup>	Acetal	33.02 1.300	27.31 1.075	14.50 .571	—	Individual (1)	1-413592-1
		BE CU, Gold (30) <sup>1</sup>	Acetal	32.54 1.281	31.12 1.225	17.15 .675	—	Bulk (100)	413366-1 <sup>1</sup> 413366-2 <sup>2</sup>
C	Brass, Nickel	BE CU, Silver (200) <sup>2</sup>	TEFLON	32.54 1.281	23.37 .923	—	—	Bulk (100)	221988-1
	Zinc, Nickel	PH BR, Gold (5C) <sup>3</sup>	Acetal	32.54 1.281	23.62 .930	—	—	Bulk (100)	414311-1

<sup>1</sup>Black insulation cover  
<sup>2</sup>Gray insulation cover  
<sup>3</sup>(Microinches min thickness)  
<sup>4</sup>(Special graphics)

**Tee Adapter Covers**

**Material** — Polypropylene, general purpose

Color	Part No.
Black	221586-1
Ivory	221586-3

