







Print

Email

Products Industries

Resources

About TE

My Account

Innovation

Support Center

📴 Share

Quick Links-

Pricing & Availability Search for Tooling

Product Feature Selector

Contact Us About This Product

Home > Products > Modular Jacks & Plugs > Product Feature Selector > Product Details

## 5406205-2 Product Details

PCB Mounted Jacks - Single Port, Multi-port and Stacked

# Product Highlights:

- Connector
- Preloaded
- Multiple Port Configuration
- 1 x 6 Jack Configuration
- Jack Type = RJ45

View all Features

TE Internal Number: 5406205-2 🥒 Active

5406205-2



Always EU RoHS/ELV Compliant (Statement of Compliance)





# Additional Information:

Product Line Information

#### Related Products:

Tooling

#### Documentation & Additional Information

#### Product Drawings:

MODULAR JACK ASSEMBLY, 6 PORT, 8 POSITION, SHIELDED,... (PDF, English)

#### Catalog Pages/Data Sheets:

None Available

#### Product Specifications:

High Performance Modular Plugs & Jacks, PCB Mounted (PDF, English)

#### Application Specifications:

Modular Jacks (PDF, English)

None Available

Instruction Sheets:

#### CAD Files:

None Available

## Product Features (Please use the Product Drawing for all design activity)

## Product Type Features:

- Product Type = Connector
- Jack Type = RJ45
- PCB Mounting Orientation = Side Entry (Right Angle)
- PCB Mount Style = Through Hole
- Termination Method to PC Board = Solder
- Performance Category = Cat 3
- LED = Without
- Grounding Options = Panel Ground and PCB Ground
- Panel Stops = Without
- Keyed = No
- Profile = Standard
- Color = Black
- Shield Material = Copper Zinc Alloy

## Mechanical Attachment:

Panel Mount Retention = Without

## **Electrical Characteristics:**

Shielded = Yes

## **Termination Features:**

Solder Tail Contact Plating = Tin over Nickel

## Dimensions:

PCB Tail Length (mm [in]) = 3.56 [0.140]

## Body Features:

- Inverted Jack Face = No
- Shield Plating = Tin over Copper
- Number of Contacts Loaded, RJ45 (8 Positions) = 8
- PCB Ground Tab Location (mm [in]) = 4.57 [0.180]

## Contact Features:

List all Documents

- Contact Plating, Mating Area, Material = Gold (50)
- Contact Base Material = Phosphor Bronze

## **Housing Features:**

- Housing Material = High Temperature Nylon
- UL Flammability Rating = UL 94V-0

## Configuration Features:

- Preloaded = Yes
- Port Configuration = Multiple
- Jack Configuration = 1 x 6
- Number of Positions = 8
- Number of Contacts Loaded = 8
- Number of PCB Ground Tabs = 3
- Number of Panel Ground Tabs = 21

## **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

## Packaging Features:

- Packaging Method = Tray
- Packaging Quantity = 15

## Product Availability:

Region = Asia, North America

## Other:

Brand = AMP

Corporate Information

About TE Investors News Room Supplier Portal

Terms & Conditions

Privacy Policy

Careers

Quick Links

Distributor Inventory Product Cross Reference Documents & Drawings

Product Compliance Support Center

Site Map

Customer Support

Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

Keep Me Informed









