



## BOARD-TO-BOARD HEADERS & RECEPTACLES



**TE CONNECTIVITY (TE)**  
**16 MODIV VRT DR CE 100/130**  
[AMPMODU](#) | [AMPMODU](#)

535542-8  
 TE Internal Number: 535542-8

Not EU RoHS or ELV Compliant  
[Find Compliant Alternatives](#)

Connector Style **Receptacle**

Centerline **2.54 mm [ .1 in ]**

Number of Positions **16**

Packaging Method **Tube, Tube/Box**

Contact Mating Area Plating Material **Gold**

✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

### Product Drawings

[RECEPTACLE ASSEMBLY, MOD IV, DOUBLE ROW, DUAL ENTRY, .100X.100CL, VERTICAL MOUNT, AMPMODU](#)

PDF  
English

### CAD Files

[3D PDF](#)  
PDF  
3D

[Customer View Model](#)  
2D\_DXF.ZIP  
English

[Customer View Model](#)  
3D\_IGS.ZIP  
English

[Customer View Model](#)  
3D\_STP.ZIP  
English

### Product Specifications

Application Specification

[AMPMODU Mod II And Mod IV Printed Circuit Board Connectors](#)  
PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Connector Style	<b>Receptacle</b>
PCB Mounting Orientation	<b>Vertical</b>
Row-to-Row Spacing (mm)	<b>2.54, 3.81</b>
Row-to-Row Spacing (in)	<b>.15</b>

	Applied Pressure	<b>Standard</b>
	Profile	<b>Low</b>
	Product Type	<b>Connector</b>
	Applies To	<b>Printed Circuit Board</b>
	Boss	<b>Without</b>
	Series	<b>AMPMODU, MOD IV</b>
	Sealed	<b>No</b>
	Connector Type	<b>Connector Assembly</b>
<hr/>		
Configuration Features	Number of Positions	<b>16</b>
	Number of Rows	<b>2</b>
	Stackable	<b>Yes</b>
<hr/>		
Electrical Characteristics	Voltage (VAC)	<b>333</b>
	Contact Resistance (M $\Omega$ )	<b>12</b>
	Insulation Resistance (M $\Omega$ )	<b>5000</b>
	Dielectric Withstanding Voltage (VAC)	<b>750</b>
<hr/>		
Contact Features	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Mating Area Plating Thickness ( $\mu$ in)	<b>30</b>
	Contact Shape	<b>Square</b>
	Contact Current Rating (A)	<b>3</b>
	Contact Type	<b>Socket</b>
	Contact Configuration	<b>Short Point</b>
	Solder Tail Contact Plating Material	<b>Tin-Lead over Nickel</b>
	Solder Tail Contact Plating Thickness ( $\mu$ m)	<b>1.27</b>
	Contact Base Material	<b>Phosphor Bronze</b>
<hr/>		
Termination Features	Termination Method to PC Board	<b>Through Hole - Solder</b>
	Termination Post Length	<b>3.3 mm [ .13 in ]</b>
<hr/>		
Mechanical Attachment	PCB Mount Retention	<b>Without</b>
<hr/>		
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Material	<b>Polyester - GF</b>
	Housing Color	<b>Black</b>
	Housing Entry Style	<b>Bottom or Top, Closed Entry</b>

Dimensions	Height	<b>5.03 mm [ .198 in ]</b>
	PCB Thickness (Recommended)	<b>1.57 mm [ .062 in ]</b>
	Tail Length (mm)	<b>3.18</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 125</b>
	High Temperature Compatible	<b>No</b>
Operation/Application	Assembly Process Feature	<b>Board Standoff</b>
	For Use With	<b>Mates with Headers</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	MIL-C-55032	<b>No</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>
Packaging Features	Packaging Method	<b>Tube, Tube/Box</b>
	Packaging Quantity	<b>28</b>
Other	Comment	<b>TE recommends mating gold or duplex plated headers with duplex plated receptacle assemblies., To obtain the minimum mating post length, add 0.51 [.020] (not including the post lead in chamfer) to the maximum point-of-contact dimension.</b>
Product Compliance	<p><a href="#">Statement of Compliance</a> PDF</p> <p><a href="#">VIEW ALL PRODUCT COMPLIANCE</a></p>	