

BNC CONNECTORS





✓ Active



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

JACK DECOUPLER PCB RTANG

DC jacks , PCF

5413524-2

TE Internal Number: 5413524-2

Always EU RoHS/ELV Compliant

Applies To Printed Circuit Board

Panel Mount Retention With

Panel Mount Retention Type Lockwasher and Nut

PCB Mount Retention With

PCB Termination Method Through Hole

Product Drawings JACK, DECOUPLER, RIGHT ANGLE, PCB, SERIES BNC

PDF (TIFF AVAILABLE)

English

JACK, DECOUPLER, RIGHT ANGLE, PCB, SERIES BNC

PDF (TIFF AVAILABLE)

English

CAD Files 3D PDF

PDF **3D**

Customer View Model

2D_DXF.ZIP English

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D_STP.ZIP English

Catalog Pages/Data Sheets Decoupled Connectors

PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features Applies To Printed Circuit Board

Sealed

RF Connector Type Decoupled BNC

No

Connector Style Jack

	PCB Mounting Orientation	Right Angle
	Dielectric Material	Polymethylpentene
	ESD Protection	Without
	Profile	Standard
	Isolated Ground	No
	Grade	Commercial
	Product Type	Connector - RF
Electrical Characteristics	50 Ohm	Yes
	75 Ohm	No
	Impedance (Ω)	50
	Capacitance (pF)	9400
	Voltage Rating (VDC)	1500
Body Features	Body Material	Zinc
	Body Plating Material	Nickel
	Clip Style	Standard
Contact Features	Center Contact Material	Phosphor Bronze
	Center Contact Plating Material	Gold
	Center Contact Plating Thickness (µin)	889
Termination Features	PCB Termination Method	Through Hole
Mechanical Attachment	Panel Mount Retention	With
	Panel Mount Retention Type	Lockwasher and Nut
	PCB Mount Retention	With
	Panel Mount	With
	Mounting Post Length	4.01 mm [.158 in]
	Mounting Post Style	Standard
Packaging Features	Packaging Method	Tube
Product Compliance	Statement of Compliance	

Product Compliance

Statement of Compliance PDF

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

