

CATALOG

Cross Reference

Competitive Products Military Spec P/Ns Tyco Brand P/Ns

Part Number Search

- Document Search
- Product Type Search
- Product Family Search
- Alphabetical Search
- RoHS/ELV Compliance & Alternates
- CAD Model Search
- Brand Search
- Tool Search
- Multiple Part Comparison
- Lead Free Solutions
- Help/Glossary

Home



Modular Plugs and Jacks	
PCB Mounted Jacks - Single Port, Multi-port and Stacked	

AMP 555153-1 ؇ <u>Active</u>

(Corporate P/N: 555153-1)

Not ELV or RoHS Compliant
Search for Compliant (RoHS/ELV)
Alternates
CAD Geometry | Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information				
General Information	eCommerce	Related Part Information		
 General Info Sales Info Assembly Subcontractors 	Pricing & Availability	✤ <u>Tooling</u>		

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

Product Photo

Panel Cutout

Searchable Features:		
Brand:	AMP	
RoHS/ELV Compliance:	Not ELV/ RoHS compliant	
Lead Free Solder Processes:	Wave solder capable to 240°C	
Product Type:	Jack	
Port Configuration:	Single	
Jack Configuration:	1 x 1	
Jack Type:	RJ45	
Number of Positions:	8	

Other Properties:		
Housing Material:	Polyester (PBT)	
Housing Material Flammability Rating:	UL 94V-0	
Flanged:	No	
Contact Material:	Phosphor Bronze	
Shield Material:	Copper Alloy	
Latch Style:	Standard	
PCB Thickness (mm [in]):	1.57 [0.062]	
Packaging Method:	Tray	
Packaging Quantity:	Bulk	

PCB Mount Angle:	Side Entry (Right Angle)
PCB Mount Style:	Thru Hole
PCB Termination Type:	Solder
Shielded:	Yes
Performance Category:	Cat 3
Height (mm [in]):	12.70 [0.500]
Inverted Jack Face:	No
LED:	Without
Number of Contacts Loaded:	8
Grounding Options:	PCB Ground
Shield Plating:	Tin-Lead
Number of PCB Ground Tabs:	2
PCB Ground Tab Location (mm [in]):	3.05 [0.120]
PCB Tail Length (mm [in]):	3.81 [0.150]
Solder Tail Plating:	Tin-Lead over Nickel
Panel Stops:	With
Contact Mating Area Plating:	Gold (50) over Nickel (50)
Keyed:	No
Profile:	Low
Panel Attachment:	Yes
IR Reflow Compatible:	No
Color:	Black

Copyright and Privacy Statement Visit Tyco International Ltd.

[Products | Catalog | Brands | Industries | Commerce | Supplier | Contact Us | About | Home]