

5554346 - 2 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



5554346 - 2

✓ [Active](#)

2.16 [.085] IDC Connectors

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Connector
- ? Number of Positions = 36
- ? Receptacle
- ? Shielded
- ? With Panel Attachment

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

<p>Product Drawings:</p> <ul style="list-style-type: none"> ? EMI RECEPTACLE ASSEMBLY, 36 POSITION, LOW PROFILE, S... (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> ? None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> ? None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>CAD Files:</p> <ul style="list-style-type: none"> ? None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> ? Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> ? Tooling
---	--

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

<p>Product Type Features:</p> <ul style="list-style-type: none"> ? Product Type = Connector ? Number of Positions = 36 ? Gender = Receptacle ? Shielded = Yes ? Mating Connector Lock = With ? Mating Connector Lock Type = Bail Lock ? Wire/Cable Type = Ribbon Cable ? Profile = Standard ? Screw Size = 4 -40 ? Shield Material = Die Cast Metal ? Boss on Shield = With ? Strain Relief Clip Material = Thermoplastic ? Color = Black ? Comment = Boss is a 1.02 [.040] shoulder on front of shield. <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> ? Panel Attachment = With <p>Termination Related Features:</p> <ul style="list-style-type: none"> ? Solder Tail Contact Plating = Gold Flash over Nickel 	<p>Body Related Features:</p> <ul style="list-style-type: none"> ? Ribbon Cable Centerline Spacing (mm [in]) = 1.27 [0.050] ? Shield Plating = Nickel <p>Contact Related Features:</p> <ul style="list-style-type: none"> ? Contact Mating Area Plating Material = Gold Flash over Palladium Nickel over Nickel, Gold over Nickel ? Contact Material = Copper Alloy <p>Housing Related Features:</p> <ul style="list-style-type: none"> ? Housing Material = Thermoplastic <p>Industry Standards:</p> <ul style="list-style-type: none"> ? RoHS/ELV Compliance = RoHS compliant, ELV compliant ? Lead Free Solder Processes = Not relevant for lead free process ? RoHS/ELV Compliance History = Always was RoHS compliant <p>Packaging Related Features:</p> <ul style="list-style-type: none"> ? Packaging Method = Preassembled ? Packaging Quantity = 500 <p>Other:</p> <ul style="list-style-type: none"> ? Brand = AMP
---	---