




### 5557572-1 Product Details

Share | Print | Email



5557572-1

TE Internal Number: 5557572-1

Active

View 3D PDF

#### PCB Mounted Jacks - Single Port, Multi-port and Stacked

Always EU RoHS/ELV Compliant (Statement of Compliance)

##### Product Highlights:

- Connector
- Preloaded
- Multiple Port Configuration
- 1 x 6 Jack Configuration
- Jack Type = RJ45

[View all Features](#)

##### Quick Links

- ▶ Pricing & Availability
- ▶ Search for Tooling
- ▶ Product Feature Selector
- ▶ Contact Us About This Product

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

#### Documentation & Additional Information

##### Product Drawings:

- MODULAR JACK ASSEMBLY, 6 PORT,8 POSITION, RIGHT ANGL... (PDF, English)

##### Catalog Pages/Data Sheets:

- None Available

##### Product Specifications:

- High Performance Modular Plugs & Jacks, PCB Mounted (PDF, English)

##### Application Specifications:

- Modular Jacks (PDF, English)

##### Instruction Sheets:

- None Available

##### CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version A1)
- 3D Model (IGES, Version A1)
- 3D Model (STEP, Version A1)

[List all Documents](#)

##### Additional Information:

- Product Line Information

##### Related Products:

- Tooling

#### Product Features (Please use the Product Drawing for all design activity)

##### Product Type Features:

- Product Type = Connector
- Jack Type = RJ45
- PCB Mounting Orientation = Side Entry (Right Angle)
- PCB Mount Style = Through Hole
- Termination Method to PC Board = Solder
- Performance Category = Cat 3
- LED = Without
- Grounding Options = PCB Ground
- Panel Stops = Without
- Keyed = No
- Profile = Standard
- Color = Black
- Shield Material = Copper Zinc Alloy

##### Mechanical Attachment:

- Panel Mount Retention = Without

##### Electrical Characteristics:

- Shielded = Yes

##### Termination Features:

- Solder Tail Contact Plating = Tin over Nickel

##### Dimensions:

- PCB Tail Length (mm [in]) = 3.56 [0.140]

##### Body Features:

- Inverted Jack Face = No
- Shield Plating = Tin over Copper
- Number of Contacts Loaded, RJ45 (8 Positions) = 8
- PCB Ground Tab Location (mm [in]) = 4.57 [0.180]

##### Contact Features:

- Contact Plating, Mating Area, Material = Gold (50)
- Contact Base Material = Phosphor Bronze

##### Housing Features:

- Housing Material = PCT GF
- UL Flammability Rating = UL 94V-0

##### Configuration Features:

- Preloaded = Yes
- Port Configuration = Multiple
- Jack Configuration = 1 x 6
- Number of Positions = 8
- Number of Contacts Loaded = 8
- Number of PCB Ground Tabs = 3

##### Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

##### Packaging Features:

- Packaging Method = Tray
- Packaging Quantity = 15

##### Product Availability:

- Region = Asia, North America

##### Other:

- Brand = AMP

#### Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

#### Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

#### Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

#### Keep Me Informed

