

a vital part of your world

Text Search:

Friday, 25 November, 2005

CATALOG

→ Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

→ Part Number Search

- Document Search
- Product Type Search
- Product Family Search
- Alphabetical Search
- RoHS/ELV Compliance & Alternates
- CAD Model Search
- Brand Search
- Tool Search
- Multiple Part Comparison
- Lead Free Solutions
- Help/Glossary

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Modular Plugs and Jacks

↳ **PCB Mounted Jacks - Single Port, Multi-port and Stacked**

AMP 557785-1 Active

Not ELV or RoHS Compliant

(Corporate P/N: 557785-1)

Search for Compliant (RoHS/ELV) Alternates

CAD Geometry | Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ➤ General Info ➤ Sales Info ➤ Assembly Subcontractors 	<ul style="list-style-type: none"> ➤ Pricing & Availability 	<ul style="list-style-type: none"> ➤ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

Product Photo

Searchable Features:	
Brand:	AMP
<u>RoHS/ELV Compliance:</u>	Not ELV/RoHS compliant
<u>Lead Free Solder Processes:</u>	Wave solder capable to 240°C
<u>Product Type:</u>	Jack
<u>Port Configuration:</u>	Single
<u>Jack Configuration:</u>	1 x 1
<u>Jack Type:</u>	RJ45
<u>Number of Positions:</u>	8
<u>PCB Mount Angle:</u>	Side Entry (Right Angle)
<u>PCB Mount Style:</u>	Thru Hole
<u>PCB Termination Type:</u>	Solder
<u>Shielded:</u>	No
<u>Performance Category:</u>	Cat 3
<u>Height (mm [in]):</u>	13.39 [0.527]
<u>Inverted Jack Face:</u>	No
<u>LED:</u>	Without
<u>Number of Contacts Loaded:</u>	8

Other Properties:	
<u>Housing Material:</u>	High Temperature Nylon
<u>Housing Material Flammability Rating:</u>	UL 94V-0
<u>Flanged:</u>	No
<u>Contact Material:</u>	Phosphor Bronze
<u>Latch Style:</u>	Standard
<u>PCB Thickness (mm [in]):</u>	1.57 [0.062]
<u>Packaging Method:</u>	Tray

<u>Grounding Options:</u>	Without
<u>PCB Tail Length (mm [in]):</u>	3.56 [0.140]
<u>Solder Tail Plating:</u>	Tin-Lead over Nickel
<u>Panel Stops:</u>	Without
<u>Contact Mating Area Plating:</u>	Gold (50) over Nickel (50)
<u>Keyed:</u>	No
<u>Profile:</u>	Standard
<u>Panel Attachment:</u>	Yes
<u>IR Reflow Compatible:</u>	Yes
<u>Color:</u>	Black

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]