


5745136-3 Product Details



5745136-3

TE Internal Number: 5745136-3



Hardware (AMPLIMITE)

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Accessory Type = Male Screw Retainers
 Thread Size = 4-40
- Screw Length = 5.08 mm
- Clear Chromate Screw Finish
- Packaging Method = Individual

Documentation & Additional Information

Product Drawings:

SCREW RETAINER, AMPLIMITE (PDF, English)

Catalog Pages/Data Sheets:

AMPLIMITE Subminiature D Connectors - Cable Connectors (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

Female Screwlock Kits and Male Screw Retainer Kits (PDF, English)

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version O)
- 3D Model (IGES, Version O)
- 3D Model (STEP, Version O)

Additional Information:

• Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Accessory Type = Male Screw Retainers
- Thread Size = 4-40

Dimensions:

• Screw Length (mm [in]) = 5.08 [0.200]

Body Features:

- Screw Finish = Clear Chromate
- Screw Plating = Zinc
- Screw Material = Cold Rolled Steel
- Retainer Clip Material = Stainless Steel

Industry Standards:

- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

For Use With = Metal Shell Connectors (HDE and HDP)

Packaging Features:

• Packaging Method = Individual

Other:

- Brand = AMP
- Comment = All parts are packaged unassembled.; Each kit is comprised of two male screws and two retaining clips. Male screw retainers are also furnished as part of cable clamp kits.; Male screw retainers mate with female screwlocks, with HDF metal-shell connectors featuring 4-40 threaded inserts and with HD metal-shell board mount connectors featuring 4-40 threaded inserts or female screwlocks.; Retaining clip must be assembled onto connector flanges with threaded hole toward wire side of connector.

