




Product Number: 61626-2

.240, .295" Centerline, 250 v, 28 A max. (.140" MATE-N-LOK)



Product Type Features:

Product Type = Contact

Wire Insulation Diameter (mm [in]) = 2.54 – 4.57 [0.100 – 0.180]

Connector Line = .140 MATE-N-LOK

Comment = HDM Applicator part number ending in -1 is used on AMPOMATOR CLS Machine with T or G Terminators, -2 is used on AMP-O-LECTRIC Model K Machine, -6 is used on AMP-O-LECTRIC Model G Machine.

Electrical Characteristics:

Voltage (VAC) = 250

Current Rating (Amps.) = 28

Termination Related Features:

Solder Tail Contact Plating = Pre-Tin

Body Related Features:

Wire Range (mm [AWG]) = 0.50-2.00² [20-14]

Contact Diameter (mm [in]) = 3.56 [0.140]

Stock Thickness (mm [in]) = 0.36 [0.014]

Contact Related Features:

Contact Type = Socket

Contact Material = Phosphor Bronze

Industry Standards:

RoHS/ELV Compliance = RoHS compliant, ELV compliant

Lead Free Solder Processes = Not relevant for lead free process

RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

Packaging Method = Strip

Other:

Brand = AMP