

APPLICATION SPECIFICATION

114-5245

AMP MINI COMMON TERMINATION (CT) CONNECTOR, 1.5MM PITCH (CRIMP TYPE)

1. SCOPE


This specification covers the requirements for crimping of 1.5mm pitch Mini CT (Common Terminated) Connector (Crimp Type) for applicator and manually operated hand tool.

2. APPLICABLE PRODUCTS

This instruction sheet is applicable to products shown below:

Contact Form	Product Part No.	Crimping Tool	Wire Size	Insulation Diameter
Strip Terminal	353907-1	Applicator	0.09mm ² ~ 0.23mm ² (AWG #28 ~ #24)	Ø0.85mm ~ Ø1.05mm
Loose Piece (L/P)	353918-1	Hand Tool		

3. NOMENCLATURE



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE BE MADE BY YOU TO OTHER THAN TYCO ELECTRONICS PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS

F	Revised	T.Q	26/6/2011	H.Hoshino
E	Revised (FP00-0278-01)		19/8/2001	PRE:
D	Revised (FP00-0270-01)	P.H.NG	16/7/2001	See Back Page
C	Revised (FJ00-1095-00)	H.H	29/6/2000	APP:
B	Revised (FJ00-0993-00)	H.H	19/6/2000	1 of 4
REV	REVISION RECORD	PRE	DATE	PAGE:





TE TE Connectivity

AMP Mini Common Termination (CT) Connector, 1.5mm Pitch Crimp Type

TITLE: **AMP Mini Common Termination (CT) Connector, 1.5mm Pitch Crimp Type**

NO: **114-5245** REV: **F**

4. CRIMPING REQUIREMENT

No.	Check Items		Crimping Requirements		Remarks
			Applicator	Hand Tool	
1	Wire Strip Length		2.1±0.2 mm		Refer to ① of Fig.1
2	Wire-End Protrusion Length		0 ~ 0.5 mm		Refer to ② of Fig.1
3	Cut-Off Tab Length		0.4 mm Max.		Refer to ③ of Fig.1
4	Bellmouth	Front	Presence of Front Bellmouth is optional		Refer to ④ of Fig.1
		Rear	0.1 ~ 0.35 mm		Refer to ⑤ of Fig.1
5	Wire Barrel Crimp		Refer Table1		Refer to ⑥ of Fig.1
6	Insulation Barrel Width		1.20mm Max		Refer to ⑦ of Fig.1
7	Insulation Barrel Crimp Height		Refer Table 1		Refer to ⑧ of Fig.1
8	Allowable Deviation after Crimping	Bend-Up 	3°Max.	5°Max.	/
9		Bend-Down 	3°Max.	5°Max.	
10		Twisting 	3°Max.	5°Max.	
11		Rolling 	5°Max.	5°Max.	

Tool mark is allowable at crimped areas and transition areas only.

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITIONS THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TYCO ELECTRONICS PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS

5. CRIMPING DATA

Table 1.

Contact Part No.	Applicator Part No.	Wire Size		Insulation Strip Length (±0.2mm)	Wire Barrel			Insulation Barrel		Finished Insulation Diameter
		No. of Wires	Size (AWG)		Crimp Width	Crimp Height (±0.03mm)	Disk Mark	Crimp Width	Crimp Height	
353907-1	937629-2	1	0.23mm ² (#24)	2.1mm	1.0mm 'F'	0.75mm	A	1.07mm 'F'	1.5mm Max.	Ø0.85mm ~ Ø1.05mm
		1	0.14mm ² (#26)			0.69mm	B			
		1	0.09mm ² (#28)			0.64mm	C			

Table 2.

Wire Size (AWG)	Crimp Tensile Strength N (kgf) Min.
24	29.4 (3.0)
26	19.6 (2.0)
28	14.7 (1.5)

Note:

- Tool mark is allowable at crimped areas and transition areas only.
- The dimensions of crimp width of wire barrel and insulation barrel are the dimensions of crimping tool.

6. EXAMPLES OF APPLICABLE WIRE

Table 3.

Wire Size	Strand / Diameter	Calculated Cross Sectional Area (mm ²)	Insulation Diameter (mm)	Application Wire
AWG #24	7/0.203	0.23	Ø0.95 ~ Ø1.05	UL-1728
AWG #26	7/0.16	0.14	Ø0.85 ~ Ø1.03	UL-10272
				UL-1061
				UL-3610
AWG #28	7/0.127	0.09	Ø0.85 ~ Ø0.95	UL-1061
				UL-3343

All wires, including the above mentioned, need to be approved prior to usage.

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE TO OTHER THAN TYCO ELECTRONICS PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS



PAGE

3 of 4

NO

114-5245

REV

F

7. VALIDATION

DR	CHK	APP
Tommy. Qian	Martin. Li	Steven. Yao

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TICO ELECTRONICS' PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TICO ELECTRONICS.



TE Connectivity

PAGE

4 of 4

NO

114-5245

REV

F