



Electronics

a vital part of your world

Find Answers:

Friday, 18 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
click here

Subminiature and Microminiature D Connectors ↳ Standard Board Mount Connectors

AMP 745073-2 [Active](#)

[Not ELV or RoHS Compliant](#)

(Corporate P/N: 745073-2)

[Search for Compliant \(RoHS/ELV\)](#)

[Alternates](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ✦ General Info ✦ Sales Info ✦ Assembly Subcontractors 	<ul style="list-style-type: none"> ✦ Pricing & Availability 	<ul style="list-style-type: none"> ✦ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:		Other Properties:	
Brand:	AMP	Sealed:	No
RoHS/ELV Compliance:	Not ELV/RoHS compliant	Application:	Standard
Lead Free Solder Processes:	Wave solder capable to 240° C, Wave solder capable to 265°C	Profile:	Standard
Number of Positions:	25	Post Size (mm [in]):	0.66 [.026]
Gender:	Plug	Contact Shape:	Round
PCB Mount Angle:	Vertical	Mounting Hole Diameter (mm [in]):	3.05 [.120]
Product Series:	HD 20	Housing Material:	Thermoplastic
		Contact Material:	Brass
		Housing Flammability Rating:	UL 94V-0

<u>Mating Connector Lock:</u>	With
<u>Mating Connector Lock Type:</u>	Female Screwlocks, Fixed
<u>PCB Retention Feature:</u>	With
<u>PCB Retention Method Feature:</u>	Mounting Holes
<u>Shell Type:</u>	All Plastic
<u>Shell Size:</u>	3
<u>Panel Attachment:</u>	No
<u>Grounding Clips:</u>	Without
<u>Termination Post Length (mm [in]):</u>	3.18 [0.125]
<u>PCB Thickness (in [mm]):</u>	0.062 – 0.093 [1.57 – 2.36]
<u>Contact Mating Area Plating:</u>	Gold (30)
<u>Solder Tail Plating:</u>	Tin-Lead over Nickel
<u>Grounding Indents:</u>	Without
<u>Grounding Straps:</u>	Without
<u>PCB Mount Style:</u>	Thru Hole
<u>Color Code:</u>	None
<u>Region:</u>	Americas

<u>Female Screwlock Material:</u>	Brass
<u>Female Screwlock Plating:</u>	Nickel over Copper Flash
<u>Comment:</u>	Plugs are preloaded with size 20 DF posted pin contacts

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]

▪