



Electronics

a vital part of your world

Find Answers:

Friday, 4 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Subminiature and Microminiature D Connectors

Hardware (AMPLIMITE)

AMP 745563-3 [Active](#)

[Not ELV or RoHS Compliant](#)

(Corporate P/N: 745563-3)

[Search for Compliant \(RoHS/ELV\)](#)

[Alternates](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> General Info Sales Info Assembly Subcontractors 	<ul style="list-style-type: none"> Pricing & Availability 	<ul style="list-style-type: none"> Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:	
Brand:	AMP
Government/Industry Qualification:	No
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Not relevant for lead free process
Product Type:	Female Screw Locks
Thread Size:	4-40 UNC
Thread Length (mm [in]):	6.35 [0.250]
Screw Length (mm [in]):	11.13 [0.438]
Screwlock Style:	Screwlock With Lockwasher and Hex Nut

Other Properties:	
Screw Plating:	Zinc
Screw Material:	Steel
For Use With:	Metal Shell and All Plastic Connectors (HDE)
Comment:	All parts are packaged unassembled. Each female screwlock kit is comprised of two assemblies. One or two flat washers may be required for panel thicknesses less than 1.52 [.060]. Female screwlocks are not recommended for panel thicknesses greater than 1.52 [.060]. Female screwlocks with 2-56 thread size are to be used with cable clamps with mounting flanges. Female screwlocks with 4-40 and

Screw Finish:	Clear Chromate
Packaging Method:	Individual Kit

M3 (Metric) thread sizes can be used with all other cable clamps. Female screwlocks mate with male screw retainers. Short female screwlocks cannot be used with HDF connectors.

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]