

CATALOG
Cross Reference

[Competitive Products](#)
[Military Spec P/Ns](#)
[Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Subminiature and Microminiature D Connectors

↳ Standard Cable Connectors


747303-3

[Active](#)

[Not ELV or RoHS Compliant](#)

(Corporate P/N: 747303-3)

[Search for Compliant \(RoHS/ELV\)](#)
[Alternates](#)
[CAD Geometry](#) | [Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ↳ General Info ↳ Sales Info ↳ Assembly Subcontractors 	<ul style="list-style-type: none"> ↳ Pricing & Availability 	<ul style="list-style-type: none"> ↳ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)
[Panel Mount Cutout Dimensions](#)
Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Not relevant for lead free process
Product Type:	Connector
Product Series:	HDF-20 (Ribbon Cable)
Number of Positions:	15
Gender:	Receptacle
Contacts:	With
Wire/Cable Type:	Ribbon Cable

Other Properties:

Profile:	Low
Ribbon Cable Centerline Spacing (mm [in]):	1.27 [0.050]
Contact Material:	Phosphor Bronze
Color:	Black
Housing Material:	Thermoplastic
Housing Material Flammability Rating:	UL 94V-0
Shell Material:	Steel
Shell Plating:	Tin
Strain Relief Part Number:	747275-3
Cover Material:	Thermoplastic

<u>Wire Termination Type:</u>	Insulation Displacement Crimp (IDC)
<u>Wire Range (mm² [AWG]):</u>	0.08 - 0.15 [28-26]
<u>Mating Connector Lock:</u>	With
<u>Mating Connector Lock Type:</u>	Mounting Holes
<u>Shell Size:</u>	2
<u>Shell Type:</u>	Full Metal Shell
<u>Contact Mating Area Plating:</u>	Gold (30)
<u>Contact Termination Area Plating:</u>	Tin Lead over Nickel
<u>Contact Size:</u>	20
<u>Grounding Indents:</u>	Without
<u>Grade:</u>	Standard

Comment:	All plug assemblies are supplied with housing and cover preassembled Mass Termination
-----------------	---

[Copyright](#) and [Privacy Statement](#)
 Visit [Tyco International Ltd.](#)

[\[Products | Catalog | Brands | Industries | Commerce | Supplier | Contact Us | About | Home \]](#)

.