

CATALOG

➔ Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- ➔ [Part Number Search](#)
- ➔ [Document Search](#)
- ➔ [Product Type Search](#)
- ➔ [Product Family Search](#)
- ➔ [Alphabetical Search](#)
- ➔ [RoHS/ELV Compliance & Alternates](#)
- ➔ [CAD Model Search](#)
- ➔ [Brand Search](#)
- ➔ [Tool Search](#)
- ➔ [Multiple Part Comparison](#)
- ➔ [Lead Free Solutions](#)
- ➔ [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Subminiature and Microminiature D Connectors

↳ **Standard Cable Connectors**

AMP 747522-1 [Active](#)

[Not ELV or RoHS Compliant](#)

(Corporate P/N: 747522-1)

[Search for Compliant \(RoHS/ELV\) Alternates](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ➤ General Info ➤ Sales Info ➤ Assembly Subcontractors 	<ul style="list-style-type: none"> ➤ Pricing & Availability 	<ul style="list-style-type: none"> ➤ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Not relevant for lead free process
Product Type:	Connector Kit
Product Series:	HDP-20
Number of Positions:	9
Shielded:	Yes
Gender:	Plug
Contacts:	Without
Mating Connector Lock:	With
Mating Connector Lock Type:	Mounting Holes
Pre-Assembled:	No

Other Properties:

Color:	Black
Shell Material:	Steel
Shell Plating:	Tin
Shield Material:	Steel
Shield Plating:	Tin-Lead
Insert Material:	Thermoplastic
Insert Flammability Rating:	UL 94V-0
Packaging Quantity:	100
Cable Diameter (Max.) (mm [in]):	8.89 [0.350]
Comment:	Components of the kits are shipped unassembled and bulk-packaged in quantities of 100 pieces. Plugs accept size 20 DF pin contacts. Maximum cable diameter after jacket and braid removed.

Shell Size:	1
Shell Type:	Full Metal Shell
Contact Size:	20
Cable Insulation Diameter (mm [in]):	4.19 – 11.56 [0.165 – 0.455]
Grounding Indents:	With
Grade:	Standard
Packaging Method:	Bulk

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]

.