

CATALOG

Cross Reference

[Competitive Products](#)
[Military Spec P/Ns](#)
[Tyco Brand P/Ns](#)



- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Subminiature and Microminiature D Connectors

↳ Standard Cable Connectors


747523-1

[Active](#)

[Not ELV or RoHS Compliant](#)

(Corporate P/N: 747523-1)

[Search for Compliant \(RoHS/ELV\)](#)
[Alternates](#)
[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ↳ General Info ↳ Sales Info ↳ Assembly Subcontractors 	<ul style="list-style-type: none"> ↳ Pricing & Availability 	<ul style="list-style-type: none"> ↳ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Not relevant for lead free process
Product Type:	Connector Kit
Product Series:	HDP-20
Number of Positions:	9
Shielded:	Yes
Gender:	Receptacle
Contacts:	Without
Mating Connector Lock:	With

Other Properties:

Color:	Black
Shell Material:	Steel
Shell Plating:	Tin
Shield Material:	Steel
Shield Plating:	Tin
Insert Material:	Thermoplastic
Insert Flammability Rating:	UL 94V-0
Packaging Quantity:	100
Cable Diameter (Max.) (mm [in]):	8.89 [0.350]

Mating Connector Lock Type:	Mounting Holes
Pre-Assembled:	No
Shell Size:	1
Shell Type:	Full Metal Shell
Contact Size:	20
Cable Insulation Diameter (mm [in]):	4.19 – 11.56 [0.165 – 0.455]
Grounding Indents:	Without
Grade:	Standard
Packaging Method:	Bulk

Comment:

Components of the kits are shipped unassembled and bulk-packaged in quantities of 100 pieces. Receptacles accept size 20 DF socket contacts. Maximum cable diameter after jacket and braid removed.

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]