



Electronics

a vital part of your world

Find Answers:

Friday, 4 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Subminiature and Microminiature D Connectors
↳ Standard Cable Connectors

749805-2 [Active](#)

[Not ELV or RoHS Compliant](#)

(Corporate P/N: 749805-2)

[Search for Compliant \(RoHS/ELV\)](#)

[Alternates](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ↳ General Info ↳ Sales Info ↳ Assembly Subcontractors 	<ul style="list-style-type: none"> ↳ Pricing & Availability 	<ul style="list-style-type: none"> ↳ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Not relevant for lead free process
Product Type:	Cable Connector and Clamp
Product Series:	HDP-20
Number of Positions:	15
Shielded:	Yes
Gender:	Plug
Contacts:	With
Wire Termination Type:	Crimp Snap

Other Properties:

Cable Clamp Type:	One-Piece Quick Snap
Cable Exit Angle:	Straight(180°)/120°
Grommets:	With
Screws and Retainer Clips:	With
Body Material:	Polypropylene
Contact Material:	Phosphor Bronze, Brass
Cable Support Gate Material:	Polypropylene
Housing Material:	Glass-Filled Nylon, Glass-Filled Polyester
Housing Flammability Rating:	UL 94V-0
Shell Material:	Steel
Shell Plating:	Tin over Copper

<u>Wire Range (mm² [AWG]):</u>	0.15 - 0.40 [26-22]
<u>Mating Connector Lock:</u>	With
<u>Mating Connector Lock Type:</u>	Mounting Holes
<u>Shell Size:</u>	2
<u>Shell Type:</u>	Front Metal Shell
<u>Contact Mating Area Plating:</u>	Gold Flash
<u>Contact Termination Area Plating:</u>	Tin, Tin-Lead
<u>Contact Size:</u>	20
<u>Cable Insulation Diameter (mm [in]):</u>	4.32 – 9.65 [0.170 – 0.380]
<u>Grounding Indents:</u>	With
<u>Grade:</u>	Standard
<u>Packaging Method:</u>	Bulk

<u>Mounting Screw Material:</u>	Steel
<u>Mounting Screw Plating:</u>	Zinc
<u>Retainer Clip Material:</u>	Stainless Steel
<u>Packaging Quantity:</u>	100
<u>Strain Relief Clip Material:</u>	Stainless Steel
<u>Screw Material:</u>	Steel
<u>Screw Plating:</u>	Zinc

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]